





ZeroSmog WE1010 **Shield** Kit at a glance

For a seamless and health-conscious soldering experience, Weller bundled its best seller WE1010NA soldering station with the new ZeroSmog Shield single filtration unit. This easy-to-use soldering bundle not only ensures precision in your soldering projects, but also prioritizes your health. The advanced filtration system efficiently captures and removes harmful fumes and particles, protecting the operator's respiratory health

With adjustable temperature control and an ergonomic design, this soldering station offers ease of use, making it ideal for beginners and seasoned professionals alike. Get your project soldered and breathe easy.



Soldering without fume extraction



Soldering with fume extraction





Easy to use soldering station plus fume extraction unit

- Maximum health protection
- Protect the operator's health and work environment with efficient particulate and gas filtration

 Healthier operators, who enjoy their work more and achieves better soldering results.



Time-Efficient Performance

- Fast soldering success with an efficient and powerful soldering and extraction system
- Save time and increase efficiency



Single User Eco-System

- Self-contained solution
- For soldering and fume extraction needs
- All in one single, easy-touse ecosystem







The WE1010 Shield kit consisting of the WE1010NA soldering station and the new Shield fume extraction system, is a cost-effective, worry-free package for getting all your soldering jobs done in an easy, efficient and healthier way. No matter if you are a professional, an advanced hobbyist or in education.

The ZeroSmog Shield is not designed for industrial use.

WE1010NA Soldering Station Get it soldered!

Digital LCD screen

For easy navigation for temperature and includes stand-by mode

Intuitive to use digital soldering station

for a wide range of prosumer and professional soldering tasks





Weller

Learn more about WE1010NA

Use **Zero**Smog

ZeroSmog Shield Fume Extraction Breathe easy!





^{*}The ZeroSmog Shield Fume Extraction Unit is only available as a bundle with the WE1010NA Soldering Station.

Protect your health during hand soldering.

Did you know that

- long and short term exposure to airborne particles and gases can lead to symptoms including dermatitis
- and acne, headaches, eye irritation, sinonasal cancer, sore throats, and lung damage*?
- at least 20 % of employees in the soldering area indicate clinical symptoms of asthma**?
- in many countries legal regulations govern clean air in the work place***?

*HSE Health & Safety Executive in Great Britain
**Results from a study made in USA & Europe
*** E.g. in Sweden and Norway

Comparison:

Influence of smog inhalation

Good reasons to use Weller ZeroSmog filtration units

- Protect your respiratory system
- · Care for health and well-being
- Stay compliant with regulations
- Take responsibility for the environment
- Reduce absence times and healthcare costs
- Increase productivity

Fibers, pollen 10 µm Bacteria, pigments 5 µm

Smog:

Asbestos dust > 10 μm Viruses > 5 μm

Gas



Weller
Protect
your health

Use **Zero**Smog





#PowerfulTogether WE1010 Shield Kit

T0053298391





*The ZeroSmog Shield Fume Extraction Unit is only available as a bundle with the WE1010NA Soldering Station.

TECHNICAL DATA SOLDERING STATION WE1010NA			
Dimensions L x W x H			
150 x 125 x 100 mm 5,91 x 4,92 x 3,94 inch			
Weight 1.9 kg			
Mains Supply Voltage			
230V / 50/60 Hz 120 V / 60 Hz 100V / 50/60 Hz			
Power consumption 85 W			
Safety class I, antistatic housing III, Soldering tool			
Temperature range 100 - 450 °C Tool dependent 200 - 850 °F			
Temperature accuracy Average tip temperature can be "offset" to +/- 5° C (+/- 9° F) at idle with no load			
Temperature stability $\pm 6 ^{\circ}\text{C} / \pm 10 ^{\circ}\text{F}$			
Subject to technical alterations and amendments.			

TECHNICAL DATA ZEROSMOG SHIELD		
Dimensions L x W x H 269.5 x 212 x 110 mm 10.6 x 8.3 x 4.3 inch		
Mains supply voltage 100-240 V AC 50/60 Hz		
Operating voltage 24 V DC		
Power consumption 10 W		
Weight 2 kg		
Safety class III		
Combined filter E10 EPA / Activated carbon foam		
Maximum vacuum 285 Pa		
Maximum airflow 26 m³/h		
Operating sound level from1 m distance 50 dBA at full speed		
Subject to technical alterations and amendments.		



WE1010NA SHIELD KIT (AVAILABLE AS BUNDLE ONLY)		
Order no.	Description	
WE1010NAS	WE1010NA 70 W Soldering Station 230V WEP70 70 W Soldering Iron PH70 Safety Rest with Sponge ETATip 0.062" / 1.6 mm Screwdriver ZeroSmog Shield EPA E10 Filter	

ACCESSORIES		
Order no.	Description	
T0058770714	WEP70TIP Retainer	
T0058770715	WEP70 Soldering Iron	
T0058770706	PH70 Safety Rest with Sponge	
TC205	Sponge replacement	
	ET Series Tips	
FT91000046	Replacement Filter EPA E10 for ZeroSmog Shield	

GERMANY

Weller Tools GmbH Carl-Benz-Straße 2 74354 Besigheim

Tel: +49 (0) 7143 580-0 Fax: +49 (0) 7143 580-108

USA

Apex Tool Group, LLC 670 Industrial Drive Lexington, SC 29072

Tel: +1 (800) 688-8949 Fax: +1 (800) 234-0472

CHINA

Apex Tool Group Room 302A, NO 177 Bibo Road Shanghai 201203

Tel: +86 (21) 60880288 Fax: +86 (21) 60880289

©2024, Apex Tool Group LLC WE1010 Shield NAM T0055753806 / 03.24