FEEL THE DIFFERENCE

THE PROVEN CHOICE. EVERY TIME.

HIGH-PRECISION TOOLS FOR MEDICAL DEVICE MANUFACTURING



FEEL THE DIFFERENCE

THE PROVEN CHOICE. EVERY TIME.

Manufactured with uncompromising Swiss quality, and **created especially for healthcare**, Weller Erem[®] tools are built to last. The signature highperformance cutters set the industry standard by providing over 1 million consistent precise and accurate movements. With state-of-the-art advanced features like Magic Spring[™], High-Precision Screw Joint, and Maximum Opening Stop Technology, Weller Erem Precision Tools provide the longest durability, highest precision and best quality on the planet.



Weller Erem products are made and manufactured with uncompromising Swiss quality, created to be strong, durable, sharp and precise



Just like a Swiss watch

Highest-quality tools and craftsmanship

> Weller Erem is a leader in the development and production of highprecision, top-quality precision tools (side and tip cutters, pliers and tweezers). Founded in Geneva, Switzerland in 1963, Weller Erem precision tools are the result of ongoing product development and innovation to meet customer demands and the requirements of modern manufacturing techniques.

Custom-made

Have a problem? We have the solution with our ability to quickly manufacture the custom tool you need.

With an estimated 2-week turnaround time, Weller Erem will customize any of our precision tools to meet your applications needs.





Tungsten-carbide cutters for the preparation of cardio-vascular stents

It is important in stent manufacture that the cut end of any wire in the lattice is as flat as possible, otherwise it will require necessary rework to the stents. Weller Erem side cutters have fine polished carbide cutting blades to accurately cut the lattice and reduce the need for rework.

THE PERFECT CUT

Strong, sharp and precise - every time

Cutter Medical Applications: Braided Mesh | Microsurgery | Surgical Accessories | Single/Multiple Pliers



Cut shape

Three blade options, including Weller Erem's exclusive Super Full Flush cut.



Semi-flush

- · Leaves a pyramidal tip at the end of the wire
- For standard jobs where the final shape does not play a significant role
- For both soft copper wires and very hard wires, such as stainless steel



- Leaves a much smaller tip at the end of the wire when compared to a Semi-Flush cut – without reducing the cutting ability
- The cutting edges are finer than on semi-flush cutters
- Effort exerted when cutting is less and the load on the component is reduced
- Flush wire ends reduce the effort needed to fit components on printed-circuit boards



Super Full Flush

- Provides absolutely flush wire ends, only offered from Weller Erem
- No rework is needed
- Cuts are absolutely precision-ground and sharpened
- Effort exerted when cutting is minimal, as is the load on the component caused by the cut
- Soldering tags in soldering-bath procedures are prevented
- Used in applications for medical technology and are suitable for soft wires





Weller Erem

Competitor

THE PERFECT COMBINATION

Precision, design, symmetry and balance

Tweezer Medical Applications: Braided Mesh | Microsurgery | Guide Wires | Surgical Accessories | Single/Multiple Pliers



BUILT TO LAST

Longest lasting durability on the planet

Plier Medical Applications: Braided Mesh | Microsurgery | Guide Wires | Surgical Accessories | Single/Multiple Pliers



| CUTTERS | 5 | | | | | | | | | | |
|--|---|---|--|-------------------|-------------------|-------------------|-------------------|------------------|----------------------|--------------------|-------------------------------|
| | | Kov | | | | | | | | Tungeten | |
| Model | Cut | Description | Applica- tions | A (in / mm) | B (in / mm) | C (in / mm) | D (in / mm) | Dental/ Ortho | Cardio- vascular* | Typical Medical | Tungsten- Carbide Steel |
| TOP SELLER | | Tip cutter - pointed relieved head The underside is relieved and facilitates | Guide Wires, Stents, Catheters, | 0.394 | 0.433 | 0.236 | 0.728 | | | | \checkmark |
| 576TX | Flush | optimum access even to extremely hard- to-reach areas. • This is the narrowest head shape | Single/Multiple Fillers, Lateral/ Internal Cuts | 10 | 11 | 6 | 18.5 | | | | |
| | | Side cutter - tapered head Series 2400 MagicSense model Jaws have straight edges and taper to a point This head shape allows access to difficult- | Stainless Steel or Nickel Titanium | 0.394 | 0.433 | 0.236 | 0.728 | | (| (| |
| | Flush | to-reach areas but reduces the cutting capacity in comparison to the same size oval head cutter Hard metal blades - smooth and precise rounded tips | Wires, Catheters, Coiled Wires | 10 | 11 | 6 | 18.5 | | | | \checkmark |
| 2422E | | Side cutter - oval head Useful in all cutting applications where easy access is given Robust and size for size offers the highest cutting capacity Ergonomic handles and the special materials ensure a soft feel, operating comfort and safety Most widely used head shape | Micro electronics | 0.472 | 0.433 | 0.236 | 0.748 | | | | |
| | Flush | | | 12 | 11 | 6 | 19 | | | × | |
| 622NB | Flush | Side cutter – pointed relieved head This is the narrowest head shape The underside is relieved and facilitates optimum access even to extremely hard-to-reach areas | | 0.236 | 0.354 | 0.236 | 0.630 | \checkmark | \checkmark | \checkmark | |
| 2622NB | | | | 6 | 9 | 6 | 16 | | | | • |
| 622TX | | Side cutter - oval head, Miniature cutter It is robust and offers the highest cutting capacity Transform cathida cutters | Guide Wires, Stents, Catheters, | 0.315 | 0.354 | 0.236 | 0.591 | | | | |
| Weite | Flush | This is the most widely used head shape Fits for all cutting applications where easy access is given | Fillers, Lateral/ Internal Cuts | 8 | 9 | 6 | 15 | | | | • |
| T622N | | Side cutter – oval head Fits all cutting applications where easy | Guide Wires, Stents, Catheters, Single/Multiple | 0.354 | 0.354 | 0.236 | 0.590 | | | | |
| Sinter V Sinterio | Flush | rus an cutumy apprications where easy access is given | Fillers, Lateral/ Internal Cuts | 9 | 9 | 6 | 15 | | | | V |
| 632NCF | Super Full Flush Super Content of the service of the serv | Tip cutter - straight short relieved head High precision for optical fibres Suitable for precision cuts of soft materials (e.g. small silicone tubes precision connector | Soft materials only. Perfect for trimming silicone material | 0.354 | 0.354 | 0.236 | 0.590 | | | | |
| A service of the serv | | miniature rubber seals or soft synthetic parts | 9 | 9 | 6 | 15 | | | | | |

| CUTTERS | 5 | | | | | | | | | | |
|----------------|---------------------|---|--|-------------------|-------------------|-------------------|-------------------|------------------|----------------------|--------------------|------------------|
| | | | Key - | | | | | | | | |
| Model | Cut | Description | Applica- tions | A (in / mm) | B (in / mm) | C (in / mm) | D (in / mm) | Dental/ Ortho | Cardio- vascular* | Typical Medical | Carbide Steel |
| 503ETST | | Tip cutter - angled wide head | Guide Wires, Stents, Catheters, | 0.354 | 0.433 | 0.236 | 0.748 | | (| | |
| | Flush | | Fillers, Lateral/ Internal Cuts | 9 | 11 | 6 | 19 | | ~ | | V |
| 7005 | | Side cutter - pointed relieved head The underside is relieved and facilitates optimum access even in extremely hard-to-reach areas This is the narrowest head shape | Micro | 0.472 | 0.433 | 0.236 | 0.748 | | | \checkmark | |
| | Super Full Flush | | electronics | 12 | 11 | 6 | 19 | | | | |
| 576TX-1 | | Side cutter - tapered head Jaws have straight edges and taper to a point Head shape allows access to difficult to reach areas but reduces the cutting capacity in comparison to the same size oval head cutter | Guide Wires, Stents, Catheters, | 0.433 | 0.433 | 0.236 | 0.011 | | | | |
| | Flush | | Fillers, Lateral/ Internal Cuts | 11 | 11 | 6 | 19 | | • | | • |
| 595T | Semi- Flush | Side cutter - tapered head The jaws of the cutter have straight edges and taper to a point This head shape allows access to difficult to reach areas but reduces the cutting capacity in comparison to the same size oval head cutter | Hard Wire - Stainless Steel 303-316, MP35N, Stents | 0.472 | 0.433 | 0.236 | 0.748 | | | | |
| Western Fem | | | | 12 | 11 | 6 | 19 | | ~ | | × |
| 599TE | | Side cutter - oval head Fits all cutting applications where easy access is given | | 0.472 | 0.433 | 0.236 | 0.748 | | | | |
| | Flush | | | 12 | 11 | 6 | 19 | | × | | × |
| 599750 | | Side cutter High precision for optical fibres Ideal for Keylar® silks. Vectran [™] cheated | Stainless Steel Coil Wires, Kevlar®, Vectran™ Braided Wires, Fiber Optics | 0.472 | 0.43 | 0.24 | 0.748 | | (| | |
| | Semi- Flush | ueual for Keviar' sinks, Véctran' sheated wires, optical fibres and small stainless wires | | 12 | 11 | 6 | 19 | | | | V |
| E147A | | Side cutter with compound action For cutting hard wires with minimal effort | Guide Wires, Stents, Catheters, Single/Multiple Fillers, Lateral/ Internal Cuts | 0.472 | 0.413 | 0.284 | - | \checkmark | | \checkmark | |
| e e | Semi- Flush | | | 12 | 10.5 | 7.2 | - | | ~ | | |



| PLIERS | | | | | | | | | | | |
|-----------------|-------------|---|---|--|-------------------|-------------------|-------------------|-------------------|-------------------|---|--|
| | Model Shape | | | | | | | | | | |
| | | | Description | Key Applications | A (in / mm) | B (in / mm) | C (in / mm) | E (in / mm) | G (in / mm) | Dimension Diagram | |
| 5528 | | Wire | Suitable for all types of insulation, Teflon®, Tetzel and optical fibres. Unique precision for damage-free stripping of fine wires Interchangeable blades Unlimited stripping length thanks to side stripping The required diameter is set by means of screws Non-reflecting surface Screwdriver and key are included Robust, high-precision tools for use in electronics and aeronautical engineering | All Types of Insulation, Teflon, Tefzel and optical fibers | 0.82 | 0.24 | 0.24 | 0.43 | 0.354 | | |
| | No. 1 | Stripper | | | 21 | 6 | 6 | 11 | 9 | $E = \frac{1}{1}$ A = Jaw length B = Width of tips C = Depth of interchangeable blade E = Total height of both tips G = Length of cutting blade | |
| | R | Tapered | Flat nose pliers with replaceable nylon jaws Non-reflecting surface, ESD-safe, high grade tool steel Nylon jaws prevent nicking and scratching | Forming and handling components - prevents scratching | 0.91 | 0.43 | 0.24 | 0.2 | 0.12 | | |
| 33TE | | | | and nicking for miniature and standard electronics | 23 | 11 | 6 | 5 | 3 | A | |
| 2411PD | | | Needle nose pliers with very precise and rounded jaws | For miniature and standard | 1.32 | 0.43 | 0.24 | 0.039 | 0.047 | CT CT | |
| | S | | Non-reflecting surface, ESD-safe | electronics | 33.5 | 11 | 6 | 1 | 1.2 | | |
| 2442P | 1 | | Flat nose pliers Pliers for miniature and standard electronics Optimized ergonomically shaped handles for increased comfort Non-reflecting surface, ESD-safe Suitable for gripping flat workpieces Smooth jaws and precision-machined edges | Every possible | 1.319 | 0.433 | 0.236 | 0.139 | 0.047 | | |
| 2442 1 2 | A STATE | | | to bend | 33.5 | 11 | 6 | 3.4 | 1.2 | A = Jaw length B = Head width | |
| 2411P | E | Needla and ha Piliers Optimi increas Non-re | Needle nose pliers with very precise, smooth and half-rounded jaws Pliers for miniature and standard electronics Ortimiend economic like based based. | Every possible wire application to bend | 1.319 | 0.433 | 0.236 | 0.039 | 0.047 | C = head thickness E = Width of tips G = Total height of both tips | |
| | | | Optimized ergonomically shaped handles for increased comfort Non-reflecting surface, ESD-safe | | 33.5 | 11 | 6 | 1 | 1.2 | | |

| | TWEEZE | RS | | | | | | | | |
|-----------|---------------|---|---|---|---------------------|--------------------|------------------|--------------------|--------------------|--------------|
| | Model | Shape | Description | Key Applications | Length (in / mm) | Weight (oz / g) | Dental /Ortho | Various Medical | Material | Head Size |
| 30SA vete | un Weder in P | Curried | Reverse-action tweezers, curved 50°, with robust pointed tips. For applications in biology, medicine, and laboratory technology Bent shape facilitates access to confined spaces Special stainless steel, nonmagnetic, non-rusting, acid-proof, heat-resistant Fibreglass handles for protection against heat Reverse clamping action for comfortably holding parts Particularly suitable for soldering and assembly jobs | Microelectronics, medicine and laboratory technology, electronic, welding | 6.142 | 1.023 | (| | Stainless Steel | Medium |
| | | | | | 156 | 29 | | | | |
| B15AGW | SW | Narrow Oblique Head Narrow Chique Head Narrow Chique Head Narrow Oblique Head Narrow Oblique Narrow Oblique Nar | Black cutting tweezers with narrow oblique head For soft wires up to dia. 0.25 mm.010 Inch. Suitable for cutting fine coft wires and | s and Super fine wire application | 4.528 | 0.917 | | \checkmark | Carbon Steel | Medium |
| | | | Small components Delivers high-precision cuts Hardened cutting edges for long service life | | 115 | 26 | | | | |

TWEEZERS

| | Model | Shape | Description | Key Applications | Length (in/mm) | Weight (oz/g) | Dental/ Ortho | Various Medical | Material | Head Size | |
|---------------|-------|------------------|---|--|--|------------------|------------------|--------------------|---|---------------------------------|------------|
| 2454011 | (m) | Straight/ Pound | Precision tweezers with flat rounded tips for gripping components Coated tips for non-stick holding of | For handling sticky adhesive | 4.724 | 0.53 | | | SS w/Teflon | N/A | |
| ZAJANU | | Straight/ Nound | self-adhesive parts Titanium stainless steel, nonmagnetic, non-rusting, acid-proof, heat-resistant | labels and ribbons | 120 | 16 | | \checkmark | Tips | N/A | |
| 5FSA, | F.SA | Straight pointed | aight pointed • Precision tweezers with extremely pointed tips for use in dissection procedures and working under a microscope • For mathematical excellent access to the most confined spaces • Stainless steel, robust tips, non-rusting, non-reflecting surface • For mathematical excellent access to the most confined spaces | For use on soft | 4.528 | 0.42 | | \checkmark | Stainless Steel | | |
| 5MBS | | | | matchais | 115 | 12 | | | | | |
| 15AGS | | Narrow Oblique | Cutting tweezers with narrow oblique head Hardened cutting edges for long | Designed for cutting fine soft wires up to dia. | 4.528 | 0.74 | | | Carbon na Steel 1 Stainless & Carbon | .216 narrowed | |
| | | Неад | Service life Suitable for cutting fine, soft wires and small components | 0.25 mm/.010 in. and small components | 115 | 21 | | • | | to a pt | |
| 29Y Series | | | Non-reflecting surface | Suitable for stripping fine | 4.724 | 0.78 | | \checkmark | Stainless & Carbon | | |
| | | | | PVC or Teflon® insulation | 120 | 22 | | | | | |
| | | Ring-Shaped | Gripping tweezers with locking mechanism The ring-shaped tip provides for secure handling up to a tensile force of 5 kg Suitable as a ligature clamp in dentistry Can be disinfected and sterilized Gripping tweezers enable the user to hold and manipulate particularly fine wires with a diameter from 0.3 mm/ .011 Inch or insulated optical fibres with a diameter of between 1.5 mm/.059 Inch and 5 mm/.197 Inch | | 4.724 | 0.60 | (| (| Stainless | | |
| 940AS | | | | | 120 | 17 | | | Steel | | |
| 7 5 4 | E. | Curred | Precision tweezers, curved, relieved, with pointed tips Bent shape facilitates access to | For applications in biology, medicine, | 4.724 | 0.53 | | | Stainlass | Very Fine | |
| | | | confined spaces Special stainless steel, nonmagnetic, non-rusting, acid-proof, heat-resistant | laboratory technology and microelectronics | 120 | 15 | | ~ | | , | |
| 554 | 5-5A | Straight | Precision tweezers with very pointed tips, suitable for very fine wires Relieved shape facilitates excellent access to the most confined spaces Snecial stanless steel non-mannetic | Micro | 4.528 | 0.42 | | | Stainless | Very Fine | |
| DSA | | Straight | special stanless steel, non-magnetic, non-rusting, acid-proof, heat-resistant For precision work e.g. under a microscope | electronics | 115 | 12 | | | Antiacid | iony i mo | |
| 25854 | 0 | Straight | Precision tweezers with pointed synthetic tips (PPS) and serrated finger grips for secure handling Relieved shape facilitates excellent | Secure handling of components up to 480F and | 4.724 | 0.53 | | | Stainless Antiacid | Fine Point | |
| 258SA | | Stra | Straight | access to the most confined spaces • Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant • For precision work e.g. under a microscope | resistant to acid and molten solder - water resistant | 120 | 15 | | | w/ pointed synthetic tips | Fine Point |



TWEEZERS

| | Model | Shape | Description | Key Applications | L (in/mm) | W (in/mm) | Dental/ Ortho | Various Medical | Material | Head Size | | | |
|-------|---------|------------|--|--|--------------|--------------|--|---|--------------------|------------|--|--|--------------------|
| 04054 | - | Chrolicht | Precision tweezers with pointed synthetic tips (PPS) and serrated finger grips for secure handling Non-reflecting surface Suitable for delicate schedard | Microelectronics, medicine and laboratory technology. Secure handling of | 5.118 | 0.71 | | | Anti-Mag- | Diuné | | | |
| 2495A | | Straight | Surtable for delicate standard applications and precision work on small components or wires Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant | components up to 480F and resistant to acid and molten solder - water resistant | 130 | 20 | | ~ | netic | Biunt | | | |
| M5S | MB-S | Straight | Micro-tweezers, very pointed tips, e.g. for precision work under a microscope Suitable for delicate standard applications and precision work on | Microelectronics, medicine and laboratory technology. For precision | 3.150 | 0.21 | | | Stainless Steel | Very Fine | | | |
| | | | small components or wires • Stainless steel, robust tips, non-rusting, non-reflecting surface | electronic application work under a microscope | 80 | 6 | | × | | | | | |
| 3CSA | tot & | Straight | Precision tweezers, standard model for delicate work Suitable for delicate standard applications and precision work on small components or wires Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant | General purpose use in microelectronics, medical and laboratories | 4.331 | 0.39 | | \checkmark | Anti-Mag- netic | | | | |
| | | | | | 110 | 11 | | | | | | | |
| 1SA | 1-50 % | Straight | Suitable for delicate standard applications and precision work on small components or wires Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant | General purpose use in microelectronics, medical and laboratories | 4.724 | 0.49 | | | Stainless Steel | Fine Point | | | |
| | | | | | 120 | 14 | | ¥ | | | | | |
| 2ASA | 2854 | Straight | Precision tweezers with flat rounded tips for gripping components. Special stainless steel, nonmagnetic, non-rusting, acid-proof, heat-resistant Suitable for all standard gripping applications and assembly jobs on printed-circuit boards | General purpose use in microelectronics, medical and laboratories | 4.724 | 0.53 | | \checkmark | Stainless Steel | Flat Round | | | |
| | | | | | 120 | 15 | | , v | | | | | |
| 3CSA | 551 (2) | Straight | Suitable for delicate standard applications and precision work on small components or wires Snecial stanless steel non-magnetic. | General purpose use in microelectronics, medical and | 4.331 | 0.39 | | \checkmark | Stainless Steel | Fine Point | | | |
| _ | - | | non-rusting, acid-proof, heat-resistant | and delicate work | 110 | 11 | | | | | | | |
| 264 | 2056 2 | Straight | Suitable for delicate standard applications and precision work on credit components or wince | General purpose use in | 4.724 | 0.49 | | (| Stainless | | | | |
| 3SA | | Straight . | Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant | medical and laboratories | 120 | 14 | | V | Steel | riie roint | | | |
| 5SA | 5 -5h | Straight | Precision tweezers with very pointed tips, suitable for very fine wires Relieved shape facilitates excellent access to the most confined excert. | For precision | 4.528 | 0.42 | | | Stainlase | | | | |
| | 5-SA | 5-5A | 5-58 | 5-54 Million | 5-SA | Suaiyill | access to the most confined spaces • Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant • For precision work e.g. under a microscope | application work under a microscope | 115 | 12 | | | Stainless Steel |

TWEEZERS

| | Model | Shape | Description | Key Appli- cations | Length (in/mm) | Weight (oz/g) | Dental/ Ortho | Various Medical | Material | Head Size | |
|-------|-------|----------|--|---|--|------------------|------------------|--------------------|-----------------------|---------------------------------|------------|
| | 26380 | | • Precision tweezers, lightly curved 15°, relieved. Very pointed tips, e.g. for installing small components | For applications in biology, medicine, | 4.528 | 0.42 | | _ | Stainless | | |
| 5ASA | | Bent | Bent shape facilitates access to confined spaces Special stainless steel, nonmagnetic, non-rusting, acid-proof, heat-resistant | laboratory technology and microelectronics | 115 | 12 | | \checkmark | Steel | Fine Point | |
| 70.4 | 5F.5A | Dant | Precision tweezers, curved, relieved, with pointed tips. Excellent handling in confined spaces Pret these foreitierts access to | For applications in biology, medicine, | 4.724 | 0.53 | | (| Stainless | Fine Deint | |
| 754 | | Dent | confined spaces Special stainless steel, nonmagnetic, non-rusting, acid-proof, heat-resistant | laboratory technology and microelectronics | 120 | 15 | | \checkmark | Steel | Fille Folili | |
| AASA | | Straight | Suitable for delicate standard applications and precision work on small components or wires Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant | General purpose use in microelectronics. | 4.921 | 0.56 | | | Stainless | Fine Point | |
| | | | | medical and laboratories | 125 | 16 | | V | Steel | | |
| | | Straight | Precision tweezers with pointed tips. Very robust. Suitable for standard applications, e.g. for assembly in electronics Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant | General purpose use in microelectronics, medical and laboratories Suitable for delicate standard applications and precision work on small components or wires | 4.724 | 0.71 | | (| Stainless Steel | Fine Point | |
| OOSA | | | | | 120 | 20 | | × | | | |
| 00054 | | Chroicht | Model same as 00SA, but with serrated finger grips and inside- serrated tips for secure handling | General purpose use in microelectronics, medical and laboratories Suitable for delivato | 4.724 | 0.71 | | | Stainless Steel | Fine Point | |
| | | Sudiyili | | standard applications and precision work on small components or wires | 120 | 20 | | V | | T Inc T Out | |
| | - E. | | Cutting tweezers with narrow oblique head. For soft wires up to dia 0.25 mm/ 010 lnch | Suitable for cutting fine, | 4.528 | 0.92 | | (| Carbon | | |
| 15AGW | | Cutting | Delivers high-precision cuts Hardened cutting edges for long service life | soft wires and small components | 115 | 26 | | ✓ | Steel | Oblique | |
| 4ASA | 5-5A | Straight | Relieved shape facilitates excellent access to the most confined spaces | For precision application | 4.331 | 0.45 | | | Stainless | Very Fine | |
| 4ASA | | Straight | Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant | work under a microscope | 110 | 13 | | V | Steel | | |
| 05000 | | | Precision tweezers with pointed synthetic tips (PPS) and serrated finger grips for secure handling Relieved shape facilitates excellent | Secure handling of components up | 4.724 | 0.53 | | | Stainless Antiacid | | |
| 258SA | | | Straight | Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant For precision work e.g. under a microscope | resistant to acid and molten solder - water resistant | 120 | 15 | | \checkmark | w/ pointed synthetic tips | Fine Point |



The Right Tool, for the Right Medical Application

Weller has a wide range of precision tools made from various material and tips

The Perfect Cut

Strong, sharp and precise - every time

Weller Erem Cutters are designed to be strong, durable and sharp, having the highest precision available.



Built to Last

The longest lasting durability on the planet

Weller Erem Pliers are designed to ensure an accurate and sure grip every time.



The Perfect Combination

Precision, design, symmetry and balance

Weller Erem has a wide range of Tweezers, each designed to be strong, comfortable and precise.



GERMANY

Weller Tools GmbH Carl-Benz-Straße 2 74354 Besigheim

Tel: +49 (0) 7143 580-0 Fax: +49 (0) 7143 580-108

Weller®

CHINA

Apex Tool Group Room 302A, NO 177 Bibo Roac Shanghai 201203

Tel: +86 (21) 60880288 Fax: +86 (21) 60880289

USA

Apex Tool Group, LLC 670 Industrial Drive Lexington, SC 29072

Tel: +1 (800) 688-8949 Fax: +1 (800) 234-0472

www.weller-tools.com