



2-Channel Power Unit, 200 W (300 W)

Item No: T0053377699N

2-Channel Power Unit, 200 W (300 W)

KEY FEATURES

- + 2 independent channels with automatic tool recognition
- + Simultaneous operation up to 2 tools
- + HAP 1 and DSX desoldering iron cannot be connected at the same time

TECHNICAL DATA

Width	240.0 mm
Height	103.0 mm
Length	280.0 mm
Dimensions L x W x H	280.0 x 240.0 x 103.0mm
Automatic Tool Identification	Yes
Capacity (l/min)	18 l/min
Desoldering	Yes
Equipotential Bonding Socket	Via 3.5mm Jack Bush (Initial State-Hard-Grounded)
ESD Safe	Yes
Hot Air (picto)	Yes
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001
Maximum Hot Air Flow Rate l/min (Depends on Tool)	10 l/min
Maximum Volume	0.7 bar
Number of Channels	2
Power	250 W (300 W)
Temperature Accuracy °C	± 9 °C
Temperature Accuracy °F	±17 °F
Temperature Accuracy for Hot Air	±30 °C
Temperature Range (Depends on Tool)	Temperature control of channels Soldering and desoldering iron stepless 50 °C - 550 °C (150 °F - 999 °F) Controllable temperature range depends on the tool
Temperature Range °C	50 - 550 °C
Temperature Range °F	150 - 999 °F
Temperature Stability °C	±2 °C
Temperature Stability °F	±4 °F
Tip Type	WT
UPC	037103305497
USB	Yes
Vacuum	0,7 bar
Voltage	230 V