



Desoldering station, 2 channels, 250 W

Item No: T0053379699N

Desoldering station, 2 channels, 250 W

KEY FEATURES

- + Power unit WR 2, 2 channels with desoldering iron DSX 80 and safety rest WDH 30
- + Repair kit for soldering and desoldering

TECHNICAL DATA

Height	102mm
Length	273mm
Dimensions L x W x H	273.0 x 235.0 x 102.0mm
Automatic Tool Identification	Yes
Capacity (l/min)	18 l/min
Desoldering	Yes
Equipotential Bonding Socket	Via 3.5mm Jack Bush (Initial State-Hard-Grounded)
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001D
Maximum Hot Air Flow Rate l/min (Depends on Tool)	10 l/min
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	2
Overcurrent Release	1,6 A
Power	300 W
Temperature Accuracy °C	± 9 °C
Temperature Accuracy °F	±17 °CF
Temperature Accuracy for Hot Air	±30 °C
Temperature Range (Depends on Tool)	Soldering and desoldering tool, continuously variable from 50 °C - 550 °C (150 °F - 999 °F) Controllable temperature range is tooldependent
Temperature Range °C	65 - 510 °C
Temperature Range °F	150 - 950 °F
Temperature Stability °C	±2 °C
Temperature Stability °F	±4 °F
UPC	037103305510
Voltage	230 V