



WXA 2

Item No: T0053425699N

2-Channel Power Unit, 200 W (255 W)

KEY FEATURES

- + Power unit with 2 channels
- + For operation with external compressed air
- + Simultaneous operation of 2 soldering tools

TECHNICAL DATA

Height	135mm
Length	174mm
Dimensions L x W x H	174.0 x 154.0 x 135.0mm
Air Consumption	20 l/min
Automatic Tool Identification	Yes
Benchtop Controller	Yes
Capacity (l/min)	20 l/min
Compressed Air Connection (Outer Diameter)	6.0mm
Compressed Air Connection Accessory	Oil free, dry compressed air

Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3.5mm Pawl Socket on Back of Device
ESD Safe	Yes
Fuse	T2A
Hot Air (picto)	Yes
Interface	1x USB, 2x RS232, 1x Switching Output
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Multilingual Display	Yes
Number of Channels	2
Operating Pressure	4 - 6 bar 54 - 87 psi
Power	200 W (255 W)
Temperature Accuracy °C	± 9 °C
Temperature Accuracy °F	±17 °F
Temperature Accuracy for Hot Air	±30 °C
Temperature Range (Depends on Tool)	Adjustable from 50°C - 550°C (150°F - 999°F) Adjustable temperature range varies among tools
Temperature Range °C	100 - 550 °C
Temperature Range °F	200 - 999 °F
Temperature Stability °C	±2 °C
Temperature Stability °F	±4 °F
Traceability	Yes
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Vacuum	-0,6 bar
Voltage	230 V
Weight (Catalog)	4.00 kg