



WSW SAC L0 1,6mm, 500g, SN3,0AG0,5CU3,5%

Item No: T0051386699

SAC L0 Solder Wire, Ø 1,6mm, 500g

Designed to enhance the quality of all your soldering jobs, Weller's WSW line of solder increases productivity, and optimizes your soldering performance. The reduced splash feature increases safety and enables you to have a cleaner work area. With a guaranteed 100% continuous flux core, combined with pure first metal melting, WSW enables long-term, highly durable solder joints without cracking, even on difficult surfaces.

KEY FEATURES

- + Diameter: 1.6 mm / 0.063 inch, Weight: 500 g / 17.637 oz
- + Alloy Sn96.5Ag3.0Cu0.5, Flux content 3.5%
- + Guaranteed 100% continuous flux core
- + 100% halogen free wire
- + Lead-free industry standard with 3% silver content
- + Reduced Fe leaching to increase tip life time and reduce tip consumption by up to 70%.
- + High soldering temperatures possible
- + Good wetting characteristics
- + Reduced splash of flux & No-Clean flux

TECHNICAL DATA

Height	63.5mm
Length	63mm
Dimensions L x W x H	63.0 x 65.0mm
Diameter	1.6 mm
RoHS Compliant	Yes
Solder Wire Ø	1.6mm
Temperature Range (Depends on Tool)	217 - 221°C
UPC	037103351913
Weight (Catalog)	0.50 kg
Product Family	WSW Solder Wire