



WSW SAC M1 0,3mm, 100g, SN3,0AG0,5CU3,5%

Item No: T0051388199 SAC M1 Solder Wire, Ø 0,3mm, 100g

Designed to enhance the quality of all your soldering jobs, Weller's WSW line of solder increases productivity, and optimizes your soldering performance. The reduced splash feature increases safety and enables you to have a cleaner work area. With a guaranteed 100% continuous flux core, combined with pure first metal melting, WSW enables long-term, highly durable solder joints without cracking, even on difficult surfaces.

KEY FEATURES

- Diameter: 0.3 mm / 0.012 inch, Weight: 100 g / 3.527 oz
- Alloy Sn96.5Ag3.0Cu0.5, Flux content 3.5%
- 🕒 Universal solder wire for various applications
- 🔁 Guaranteed 100% continuous flux core
- Lead-free industry standard with 3% silver content
- Reduced Fe leaching to increase tip life time and reduce tip consumption by up to 70%.
- High soldering temperatures possible
- Very fast wetting even on difficult surfaces, as dirty and oxidized materials
- Excellent melting characteristics
- 🕒 Reduced splash of flux & No-Clean flux

Height 63.5mm Length 63mm Dimensions L x W x H 63.0 x 65.0mm Diameter 0.3 mm **RoHS** Compliant Yes Solder Wire Ø 0.3mm 217 - 221°C Temperature Range (Depends on Tool) 217-221 °C Temperature Range °C 422.6-429.8 °F Temperature Range °F UPC 037103351883 Weight (Catalog) 0.10 kg **Product Family** WSW Soldering Wire

TECHNICAL DATA