



## Zero Smog 4V for Glue Fumes

Item No: T0053661699N

Fume extraction unit Zero Smog 4V

The fume extraction unit Zero Smog 4V (ZS 4V) is adapted with a wide band gas filter to exhaust adhesive fume at gluing applications. A powerful, maintenance-free turbine provides continuous fume extraction at a maximum air extraction rate of 230 m<sup>3</sup>/h. With setting constant flow control the adjustable turbine speed avoiding unnecessary waste of suction power and saving energy.

## KEY FEATURES

- + Unit purifies air at up to 4 workplaces
- + Constant Flow Control (CFC) guarantees automatic air flow regulation for each working place independent of the connected workplaces
- + Electronic filter control with optical and acoustical filter alarm
- + Efficiency test via USB port
- + 4 casters to allow easy movement of the unit
- + Low noise level
- + 4 kits available
- + The fume extraction unit Zero Smog 4V (ZS 4V) is adapt with a wide band gas filter to exhaust adhesive fume at gluing applications. A powerful, maintenance-free turbine provides continuous fume extraction at a maximum air extraction rate of 230 m<sup>3</sup>/h. With setting constant flow control the adjustable turbine speed avoiding unnecessary waste of suction power and saving energy.

## TECHNICAL DATA

Width	325.0mm
Capacity (m <sup>3</sup> /h)	230 m <sup>3</sup> /h
Compact Filter	Broadband gas filter (50% activated carbon + 50% Chemisorb)
Compatible Nozzle	WX WT
ESD Safe	Yes
Maximum Blower Vacuum (Pa)	3,800 Pa
Maximum Capacity	1-4 Workstations
Power	275 VA
UPC	037103273444
USB	The USB port can be used to load firmware updates, run efficiency tests and log data. Do not leave the USB medium inserted for longer than 2 minutes. After this time expires, the USB module will switch off automatically.
Weight (Catalog)	19.00 kg
Product Family	ZeroSmog TL Glue Fumes Kit