



Fume extraction Zero Smog 6V for adhesive fumes

Item No: T0053667699N

Fume extraction Zero Smog 6V for
adhesive fumes

KEY FEATURES

- + Unit purifies air at up to 8 workplaces
- + The Constant Flow Control (CFC) guarantees optimal air flow regulation for each working place independent of the connected workplaces
- + Efficiency test via USB port
- + Electronic filter control with optical and acoustical filter alarm
- + 4 wheels to allow easy movement of the unit
- + Remote control via RS 232 port
- + Low noise level
- + The fume extraction system Zero Smog 6V with gas filter could be used to extract adhesive fumes. The unit is user-friendly with quick and simple installation and filter exchange. It has a low noise emission level and is small and convenient to locate within the work area. The high quality components used in the ZS 6V result in low servicing requirements and long system life. To increase filter lifetime and save on energy, the ZS 6V is fitted with a constant flow control (CFC) – depending on the number of connected workplaces. To extend the capacity an external.

TECHNICAL DATA

Width	460.0 mm
Height	665.0 mm
Length	460.0 mm
Dimensions L x W x H	460.0 x 460.0 x 665.0mm
Compact Filter	Particle filter H13, broadband gas filter (50% activated carbon + 50% Chemisorb)
Compatible Nozzle	WX WT
ESD Safe	Yes
Maximum Blower Vacuum (Pa)	3,000 Pa
Maximum Capacity	1-8 Workstations
Power	460 VA
UPC	4003019428779
USB	The USB port can be used to load firmware updates, run efficiency tests and log data. Do not leave the USB medium inserted for longer than 2 minutes. After this time expires, the USB module will switch off automatically.