



## WXD2 230V

Item No: T0053426399N

2-Channel Power Unit, 200 W (255 W)

## KEY FEATURES

- + Cost effective because only one station is needed
- + Less rework by optimal use of tools and the correct working temperature. Reduction of running costs by longer tip lifetime.
- + Desoldering iron with stand-by mode
- + ESD safe
- + For operation with external compressed air

## TECHNICAL DATA

Height	135mm
Length	174mm
Dimensions L x W x H	174.0 x 154.0 x 135.0mm
Air Consumption	35 l/min
Air Pressure	58 - 87 psi
Automatic Tool Identification	Yes

Benchtop Controller	Yes
Compressed Air Connection (Outer Diameter)	6.0mm
Compressed Air Connection Accessory	Oil free, dry compressed air
Desoldering	Yes
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3.5mm pawl socket on back of device
ESD Safe	Yes
Fuse	T2A
Interface	1x USB, 2x RS232, 1x Switching Output
IPC Compliant	Yes
Noise level (distance 1 m) dB(A)	0.7 bar
Multilingual Display	Yes
Number of Channels	2
Operating Pressure	4 - 6 bar 54 - 87 psi
Power	200 W (255 W
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range (Depends on Tool)	Adjustable from 50°C - 550°C (150°F - 999°C)Adjustable temperature range varies among tools
Temperature Range °C	50 - 550 °C
Temperature Range °F	150 - 999 °F
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
Traceability	Yes
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Vacuum	0.5 bar (55 kPA) (8 psi)
Voltage	230V
Weight (Catalog)	3.80 kg
Product Family	Rework, Hot Air, Desoldering Stations