

WXD2010 Set 230V

Item No: T0053428399N



KEY FEATURES

- + Desoldering station WXD 2, 2 channels with desoldering iron WXDP 120
- + Soldering- and desoldering tools with intelligent WX technology
- + Connection to external compressed air supply required
- + Energy effective: automatic stand-by mode for tools
- + Patented, ESD safe glass display. Simple and fast setting of soldering parameter.

TECHNICAL DATA

Height	135mm
Length	174mm
Dimensions L x W x H	174.0 x 154.0 x 135.0mm
Air Consumption	35 l/min
Air Pressure	58 - 87 psi
Desoldering	Yes
Equipotential Bonding Socket	Via 3.5mm pawl socket on back of device
ESD Safe	Yes
Fuse	T2 A
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	2
Operating Pressure	4 - 6 bar 54 - 87 psi
Power	200 W (255 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range (Depends on Tool)	Adjustable from 50°C - 550°C (150°F - 999°C) Adjustable temperature range varies among tools
Temperature Range °C	50-550 °C
Temperature Range °F	150-999 °F
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Voltage	230V
Weight (Catalog)	3.20 kg
Product Family	Rework, Hot Air, Desoldering Stations