

WXD 2020

Item No: T0053429399N



KEY FEATURES

- + Soldering and desoldering station WXD 2, 2 channels with WXDP 120 and soldering iron WXP 120
- + Soldering- and desoldering tools with intelligent WX technology
- + Connection to external compressed air supply required
- + Energy effective: automatic stand-by mode for tools
- + Patented, ESD safe glass display. Simple and fast setting of soldering parameter.

TECHNICAL DATA

Height	135mm
Length	174mm
Dimensions L x W x H	174.0 x 154.0 x 135.0mm
Air Consumption	35 l/min
Air Pressure	58 - 87 psi
Desoldering	Yes
Equipotential Bonding Socket	Via 3,5 mm pawl socket on back of unit.
ESD Safe	Yes
Fuse	T2 A
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	2
Operating Pressure	4 - 6 bar 54 - 87 psi
Power	200 W (255 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range (Depends on Tool)	Adjustable from 50°C - 550°C (150°F - 999°C) Adjustable temperature range varies among tools
USB	USB interface in front of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Voltage	230 V
Weight (Catalog)	3.80 kg
Product Family	Rework, Hot Air, Desoldering Stations