



#### RTWPS 002 S X

Item No: T0050115699 Pair of Pico Soldering and Desoldering Tips, 2 x 40 W, 12 V

Production within the electronics, medical technology and aerospace industries is moving faster than ever before, as components have become smaller and more sensitive. With a new generation of RTWPS Pico Tips, Weller meets these increasing demands with its Pico tweezers desoldering tips which provide an optimized heat transfer with 2 x 40W maximum power, 12V performance for very small to small components (XS to S). Lock functions make the soldering processes repeatable and transparent. Weller offers a selection of smallest smart soldering tips for pico applications. The parallel sliding block allows for increased productivity with the pre-adjusted ready-to-use pairwise tip design.

#### **KEY FEATURES**

- High-Performance / High-Productivity
  - Extremely short heat-up time: 5 sec.
  - Quick response time

### 🕂 Highest Precision

- Maximum precision during the soldering process with short tip-to-grip distance and optimized tip design.

- Precise positioning ensured with unique parallel sliding block guide.
- No alignment necessary after tip change with pairwise design
- Adjustability functions with Allen key: 1.5mm possible if needed

 $(\pm 80^{\circ} \text{ rotation angle adjustment} + \text{vertical length adjustment of } \pm 1.2 \text{mm})$ 

- Desoldering Tweezers Tips allow Automatic Tip-Offset
- 🕒 Fastest Tweezers Tip Change

Active Tip Cartridge System allows for easy exchange of soldering tip even with a hot desoldering tweezer, all without needing an extra tool or further adjustment

# Ergonomics Improved comfort and safe handling with new ergonomic soft grips

Unique intelligent Tweezers tips
For use with WXsmart Tweezers WXMTS only

- Automatic Smart Tweezers Tip Identification
- Full Traceability with Tweezers Tip ID Number and Integrated Data Storage
- Accurate Data Results with Tip-Offset Function
- Full Process Control with Tip Lock Function

## **TECHNICAL DATA**

Length	16.2mm
Approximate Heating Time (50–350 °C/120–660 °F)	5 sec
ESD Safe	Yes
Power Consumption	2 x 40 W
Temperature Range °C	100 - 450
Temperature Range °F	200 - 850
Tip Range	RTWPS
Tip Shape	Chisel
Tip Width	0.2
UPC	037103371362
Voltage	12 VAC
Works With	WXMTS and WTMT
Product Family	SMART RTWPS Desoldering Tweezers Tips