



PUWAD101 230V

Item No: T0053268699N

Power Unit 105 W

Digital microprocessor control and the ability to use external compressed air or gas give this 105-watt hot air station amazing performance and versatility.

KEY FEATURES

- + Powerful (100 W) HAP1 pencil precisely delivers hot air to small SMT parts, reducing the risk of damage to adjacent components
- + Finger-activated hot air switch on pencil provides exceptional control
- + Digital temperature control has easy-to-read LED display for fast and accurate temperature set
- + Optional WCB1 programming module provides temperature lock-out for process control, temperature set-back for extended tip life, and °F to °C conversion
- + Hot air pencil uses HAP nozzles

TECHNICAL DATA

Width	135.0mm
Height	102.0mm
Length	175.0mm
Dimensions L x W x H	175.0 x 135.0 x 102.0mm
Air Consumption	10 l/min
Capacity (l/min)	10 l/min
Equipotential Bonding Socket	Via 3.5mm jack bush (initial state-hard-grounded)
Hot Air (picto)	Yes
Maximum Hot Air Flow Rate l/min (Depends on Tool)	10 l/min
Operating Pressure	4 bar 58 psi
Power	105 W
Temperature Accuracy °C	± 9°C, ± 30°C
Temperature Accuracy °F	± 48.2°F, ± 86°F
Temperature Range °C	50 - 450 °C (550) °C
Temperature Range °F	122 - 842 °F (1022) °F
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
UPC	037103305381
Weight (Catalog)	2.40 kg
Product Family	WT Line Soldering Stations