

WX 1011

Item No: T0053419399N



KEY FEATURES

- Power unit WX 1 with 1 channel, micro soldering iron WXMP
- Innovative operation concept
- Robust touch screen with ESD safe glass
- 1 Intuitive use with turn-click-wheel with enter key and finger guide
- Blue LED backlighting
- Multilingual menu navigation
- High functionality
- No safety rest with Stop & Go function needed thanks to integrated acceleration sensor
- Optimized precision, better stability by sensor in the soldering iron
- Specific parameterization of tool by storage medium in hand piece

TECHNICAL DATA

Height	130mm
Length	170mm
Dimensions L x W x H	170.0 x 151.0 x 130.0mm
Automatic Tool Identification	Yes
Benchtop Controller	Yes
ESD Safe	Yes
Fuse	T2A
Interface	1x USB, 2x RS232, 1x Switching Output
Multilingual Display	Yes
Number of Channels	1
Power	200 W
Temperature Accuracy °C	±9 °C
Temperature Accuracy °F	±17 °F
Temperature Range (Depends on Tool)	Adjustable from 50°C - 550°C (150°F - 999°F) Adjustable temperature range varies among tools
Temperature Range °C	100 - 550 °C
Temperature Range °F	200 - 999 °F
Temperature Stability °C	±2 °C
Temperature Stability °F	±4 °F
Traceability	Yes
USB	USB interface in front of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Voltage	230 V
Weight (Catalog)	3.20 kg