

WX2020 Set 230V



Item No: T0053421399N

2-Channel Power Unit, 200 W (255 W)

KEY FEATURES

- + Power unit WX 2, with 2 channels, 2 soldering irons WXP 120 and 2 safety rests WSR 201
- + Robust touch screen with ESD safe glas
- + Intuitive use with turn-click-wheel with enter key and finger guide.
- + Blue LED backlighting
- + Multilingual menu navigation
- + High functionality
- + No safety rest with Stop & Go function needed thanks to integrated acceleration sensor
- + Optimized precision, better stability by sensor in the soldering iron
- + Specific parameterization of tool by storage medium in hand piece
- + Visual process control via blue LED ring light

TECHNICAL DATA

| | |
|-------------------------------------|--|
| Height | 135mm |
| Length | 174mm |
| Dimensions L x W x H | 174.0 x 154.0 x 135.0mm |
| Automatic Tool Identification | Yes |
| Benchtop Controller | Yes |
| Equipotential Bonding | Yes |
| Equipotential Bonding Socket | Via 3.5mm pawl socket on back of device |
| ESD Safe | Yes |
| Fuse | T2A |
| Interface | 1x USB, 2x RS232, 1x Switching Output |
| Multilingual Display | Yes |
| Number of Channels | 2 |
| Power | 200 W (255 W) |
| Temperature Accuracy °C | ± 9°C |
| Temperature Accuracy °F | ± 17°F |
| Temperature Range (Depends on Tool) | Adjustable from 50°C - 550°C (150°F - 999°F) Adjustable temperature range varies among tools |
| Temperature Range °C | 100 - 550 °C |
| Temperature Range °F | 200 - 999 °C |
| Temperature Stability °C | ± 2°C |
| Temperature Stability °F | ± 4°F |
| Traceability | Yes |
| USB | USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types |
| Voltage | 230V |
| Weight (Catalog) | 3.45 kg |
| Product Family | WX Line Soldering Stations |