



ZeroSmog Guard 2 120 V

Item No: FT91022299

ZeroSmog Guard 2 - Dual User
Filtration Unit 146 W, 120 V

ZeroSmog Unit Guard 2, 120 V
1 x main filter (HEPA H13 and
Activated Carbon + Potassium
Permanganate)
5 x ePM1-75% prefilters

KEY FEATURES

- + Highest level filtration – for cleaner and healthier air
 - High efficiency particle and gas filtration
 - Odour removal during soldering
 - Powerful blower maintains suction pressure throughout the filter's life
 - High flow rate to collect all the smoke
 - Filter condition monitoring to ensure timely filter change
 - Bright light bar indicates status of the extraction unit
 - Quiet - lowest noise level on the market – less than 55dB
 - Easy main and pre-filter change
 - Low maintenance
 - Easy-to-reach on/off switch
 - ESD safe
 - Retains Weller Easy-Click 60 Hose system
- + Clean & Healthy Air
 - Provides superior air quality through high-efficiency filtration of soldering particles and gases with a large filtering surface (H13 HEPA particle filter, activated carbon).
- + Superior Experience
 - Lowest noise level on the market ensures a healthy, pleasant, and comfortable working environment.
- + Quick and Easy Filter Change
 - Ensures user convenience with fast, hassle-free replacements of both, prefilter and main filter.
- + Compact Design
 - Saves space with a compact, under-the-bench design ideal for single-user use.
- + Powerful Extraction
 - The robust blower maintains sufficient suction pressure throughout the filter's life, ensuring a high flow rate to capture all smoke effectively.
- + Maximum Control
 - Filter condition monitoring to ensure timely changes, as a full filter cannot clean the air effectively.
- + ZeroSmog Unit Guard 2, 120 V
 - 1 x main filter (HEPA H13 and Activated Carbon + Potassium Permanganate)
 - 5 x ePM1-75% prefilters

TECHNICAL DATA

Dimensions L x W x H	270 x 336 x 435 mm 10.63 x 13.23 x 17.13 in
ESD Safe	Yes
Maximum Capacity	200 (m³/h)
Maximum Vacuum	2250 Pa/V
Noise level (distance 1 m) dB(A)	less than 55 dBA
Power	146 W (100-120 V~)
UPC	037103378842
Voltage	100-120V (50/60 Hz)
Weight (Catalog)	9.5 kg
Product Family	Solder Fumes Volume Extraction 1-2 Workstations