



WT2023M Set 230V

Item No: T0053462699

2 Channel Rework Kit, 150 W, 230 V

Compact. Powerful. Versatile. Boost your productivity. Discover the WT2M Soldering Station, a true workaholic boosting your workspace productivity. This isn't just a tool—it's your ultimate partner for excellence. With extremely fast heat-up and recovery times, it handles everything from small components to large applications effortlessly. No more juggling tools or compromising performance. Enjoy the best value without sacrificing quality, gaining the flexibility and productivity to simplify your tasks and achieve more. Choose worry-free precision. Choose unstoppable productivity. Choose Weller WT Soldering Stations.

KEY FEATURES

- + This kit is built to handle micro and standard rework applications effectively.
- + Compact
The WT2M is a compact, dual-channel soldering station that streamlines your workspace, cuts costs, and boosts efficiency by effortlessly managing tasks from nano to larger micro applications.
- + Powerful
The Weller RTM and RTW active tips series with extremely fast heat-up times boost productivity. They allow continuous workflow and faster task completion, which ultimately leads to higher efficiency and greater project throughput.

- + Versatile**
 The WT2M soldering stations offer exceptional flexibility, seamlessly integrating with both new nano and micro tools with active tip technology and existing ones with passive tip technology, ensuring a flexible, user-friendly experience for all your soldering needs. It is up to your productivity and total cost of ownership preferences.
- + Fast Heat Up and Recovery Time**
 5 seconds heat-up time with Weller's RT tips with active heat technology. Fast heat-up times maximize productivity by reducing waiting periods, enabling quicker start times, continuous workflow, and faster job completion, enhancing overall efficiency and performance.
- + Multiple Options possible**
 Connect 10+ different soldering tools to one WT1M soldering station, showcasing unmatched flexibility. Fast and powerful active tips or cost of ownership sensitive tools enhance efficiency without the need for multiple stations.
- + Stackable units**
 WT stations can be stacked onto each other
- + Health Care**
 The WT station, connected to a Weller ZeroSmog fume extraction unit, safeguards health during soldering.
- + 2 Channel Rework Kit (150 W) to cover micro and standard soldering and desoldering tasks**
 including WTMP MS Micro pencil and WTMT MS Micro tweezers with active (cartridge) tip technology
 RTM and RTW Tip Family 5 seconds heat-up time
 High productivity
 Intuitive use thanks to clear menu structure
 Reduced footprint thanks to stackability
 Graphical backlit LC-Display
 High performance and functionality - many connectable tools
 Housing cover useable as storage
 OFF time, Process window, Lock function, Offset
 Stackable units
 Connectable to ZeroSmog Fume Extraction Units
 Station Set to cover smallest to standard rework tasks
 Micro desoldering tools with active (cartridge) tips
 5 seconds heat-up time
 Stackable units
 Connectable to ZeroSmog Fume Extraction Units
- + 2 Channel Rework Kit (150 W) to cover micro and standard soldering and desoldering tasks**
 including WTMP MS Micro pencil and WTMT MS Micro tweezers with active

(cartridge) tip technology
RTM and RTW Tip Family 5 seconds heat-up time
High productivity
Intuitive use thanks to clear menu structure
Reduced footprint thanks to stackability
Graphical backlit LC-Display
High performance and functionality - many connectable tools
Housing cover useable as storage
OFF time, Process window, Lock function, Offset
Stackable units
Connectable to ZeroSmog Fume Extraction Units
Station Set to cover smallest to standard rework tasks
Micro desoldering tools with active (cartridge) tips
5 seconds heat-up time
Stackable units
Connectable to ZeroSmog Fume Extraction Units

Compact. Powerful. Versatile



TECHNICAL DATA

Dimensions L x W x H	150 x 130 x 101 mm
ESD Safe	Yes
Fuse	T 0,8
Mil-Spec	Yes
Power Consumption	150 W
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range (Depends on Tool)	100 - 450 / 550 °C
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
UPC	4003019449361
Voltage	230V (50 Hz)
Weight (Catalog)	1.9 kg
Product Family	WT Line Soldering Stations