


## WR3000MER Set 230V





## **KEY FEATURES**

- Power unit WR 3M, 3 channels with soldering iron WP 120, desoldering iron DSX 120 and hot air iron HAP 200
- Large all round set for all repair jobs
- Desoldering iron DSX 120 for horizontal applications

## **TECHNICAL DATA**

Height	103mm
Length	280mm
Dimensions L x W x H	280.0 x 240.0 x 103.0mm
Capacity (l/min)	18 l/min
Desoldering	Yes
Equipotential Bonding Socket	Via 3.5mm jack bush (initial state-hard- grounded)
Hot Air (picto)	Yes
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001D
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Number of Channels	3
Overcurrent Release	2.0 A
Power	400 W
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range °C	50 - 550 °C
Temperature Range °F	150 - 950 °F
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
USB	Yes
Vacuum	0.7 bar (79 kPA) (8 psi)
Voltage	230V
Weight (Catalog)	7.30 kg
Product Family	Rework, Hot Air, Desoldering Stations