

WR2000A Set 230V

Item No: T0053378699N

2-Channel Rework Station Set, 200 W
(300 W)



KEY FEATURES

- + Hot air station WR 2, 2 channels with hot air iron HAP 1
- + Small hot air set
- + Simultaneous operation of 2 soldering tools
- + All soldering tools up to 200 W connectable

TECHNICAL DATA

Height	103mm
Length	280mm
Dimensions L x W x H	280.0 x 240.0 x 103.0mm
Automatic Tool Identification	Yes
Capacity (l/min)	18 l/min
Equipotential Bonding Socket	Via 3.5mm jack bush (initial state-hard-grounded)
ESD Safe	Yes
Hot Air (picto)	Yes
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001
Maximum Hot Air Flow Rate l/min (Depends on Tool)	10 l/min
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	2
Overcurrent Release	1,6 A
Power	250 W (300 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Accuracy for Hot Air	± 30°C, ± 54°F
Temperature Range (Depends on Tool)	Temperature control of channels Soldering and desoldering iron stepless 50 °C - 550 °C (150 °F - 999 °F) Controllable temperature range depends on the tool.
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
Tip Type	WT
UPC	037103305503
Vacuum	0,7 bar
Voltage	230V
Weight (Catalog)	5.60 kg
Product Family	Rework, Hot Air, Desoldering Stations