


## WSW SC L0 1,2mm, 500g, SN0,7CU3,5%

Item No: T0051387799
SC L0 Solder Wire, Ø 1,2mm, 500g

Designed to enhance the quality of all your soldering jobs, Weller‘s WSW line of solder increases  productivity, and optimizes your soldering performance. The reduced splash feature increases safety and enables you to have a cleaner work area. With a guaranteed 100% continuous flux core, combined with pure first metal melting, WSW enables long-term, highly durable solder joints without cracking, even on difficult surfaces.

## KEY FEATURES

- Diameter: 1.2 mm / 0.047 inch, Weight: 500 g / 17.637 oz
- Alloy Sn99.3Cu0.7, Flux content 3.5%
- 100% halogen free wire
- Silver free alloy = cost effective
- Guaranteed 100% continuous flux core
- Reduced Fe leaching to increase tip life time and reduce tip consumption by up to 70%.
- Good wetting characteristics
- Reduced splash of flux & No-Clean flux

## TECHNICAL DATA

| | |
|---|---|
| Height | 63.5mm |
| Length | 63mm |
| Dimensions L x W x H | 63.0 x 65.0mm |
| Diameter | 1.2 mm |
| RoHS Compliant | Yes |
| Solder Wire Ø | 1.2mm |
| Temperature Range (Depends on Tool) | 227°C |
| Temperature Range °C | 232 °C |
| Temperature Range °F | 442.8 °F |
| UPC | 037103352057 |
| Weight (Catalog) | 0.50 kg |
| Product Family | WSW Soldering Wire |