



WSB80 Soldering Bath

Item No: T0052704099N

Soldering bath 80 W, 24 V

KEY FEATURES

- + WSB80 Solder Bath 80 W - 24 V
- + Accessory for WT series soldering stations and WR series rework stations
- + For tin coating and preparation of small electronics components and leads
- + Precision temperature control / 150° F - 850° F / 50° C - 450° C
- + Heated surface - 80 W: Soldering bath - Ø 0.8"; x 0.98"; D / Ø 20.3 mm x 24.9 mm D
- + For lead free solder
- + Heat-up time ~ 7 min (50 °C - 350 °C)
- + For lead free solder

TECHNICAL DATA

| | |
|---|-----------------------------------|
| Height | 70mm |
| Length | 150mm |
| Dimensions L x W x H | 150.0 x 120.0 x 70.0mm |
| Approximate Heating Time (50-350 °C/120-660 °F) | 7 min |
| ESD Safe | Yes |
| Power | 80 W |
| Temperature Range (Depends on Tool) | 50 - 450 °C (150 - 850 °F) |
| Temperature Range °C | 50 - 450 °C |
| Temperature Range °F | 150 - 650 °F |
| UPC | 037103304056 |
| Voltage | 24V |
| Works With | WT1M, WT1H, WT2M |
| Product Family | Soldering Baths/Soldering Inserts |