


WSB150 Soldering Bath

Item No: T0052704299N
Soldering bath 150 W, 24 V

KEY FEATURES

- WSB150 Soldering Bath 150 W, 24 V
- Connectable to all Weller 150 W digital stations and WR3M
- For tin coating and preparation of electronics components and leads
- Precision temperature control / 150° F - 850° F / 50º C - 454º C
- Heated surface - 150 W: Soldering bath - 2.3"; x 1.2"; x 0.75"; / 58 mm x 30 mm x 19 mm
- For lead-free and leaded solder
- Heat-up time ~ 10 min (50°C - 350°C)

TECHNICAL DATA

Height	54mm
Length	175mm
Dimensions L x W x H	175.0 x 120.0 x 54.0mm
Approximate Heating Time (50–350 °C/120–660 °F)	10 min
ESD Safe	Yes
Power	150 W
Soldering Bath Dimensions (L x W x H)	57.9 x 33.0 x 19.0mm
Temperature Range (Depends on Tool)	65 - 454°C
Temperature Range °C	66 - 454 °C
Temperature Range °F	150 - 850 °F
UPC	037103304728
Voltage	24V
Works With	WT1H, WT2M, WR2, WR3M
Product Family	Soldering Baths/Soldering Inserts