



## WXS200 Soldering Bath

Item No: T0052704399N

Soldering bath 200 W, 24 V

### KEY FEATURES

- + WXS200 Soldering bath 200 W - 24 V
- + Accessory for WX / WXD and WXA series soldering, desoldering and hot air stations
- + For tin coating and preparation of electronics components and leads
- + Precision temperature control / 200° F - 930° F / 100° C - 500° C
- + Heated surface - 200 W: Soldering bath - 2.3"; x 1.2"; x 0.75"; / 58 mm x 30 mm x 19 mm
- + Heat-up time ~ 10 min (50°C - 350°C)
- + For lead free solder

## TECHNICAL DATA

Height	54mm
Length	175mm
Dimensions L x W x H	175.0 x 120.0 x 54.0mm
Approximate Heating Time (50-350 °C/120-660 °F)	10 min
ESD Safe	Yes
Power	200 W
Soldering Bath Dimensions (L x W x H)	57.9 x 33.0 x 19.0mm
Supply Unit	WX1 WX2 WXA2 WXD2 WXR3
Temperature Range (Depends on Tool)	100 - 500 °C (200 - 930 °F)
Temperature Range °C	100 - 500 °C
Temperature Range °F	200 - 930 °F
UPC	4003019423408
Voltage	24V
Works With	WXsmart, WX2, WXR, WXD2
Product Family	Soldering Baths/Soldering Inserts