



Zero Smog 4V Kit 2 Nozzle

Item No: T0053665699N

Fume extraction Zero Smog 4V with Kit 2 Nozzle

The "Zero Smog 4V Kit 2 Nozzle" fume extraction unit is easy to install and operate. It is designed for use as a small central system. The kit is supplied complete with 2 pieces: flexible hose, flex arm, nozzle, valve and bracket. Ready for installation at the workplace. A powerful, maintenance-free turbine provides continuous fume extraction at a maximum air extraction rate of 230 m³/h. With constant flow control the turbine speed is automatically adjusted to demand, avoiding unnecessary waste of suction power resulting in energy savings.

KEY FEATURES

- + Unit purifies air at up to 4 workplaces
- + Constant Flow Control (CFC) guarantees automatic air flow regulation for each working place independent of the connected workplaces
- + Electronic filter control with optical and acoustical filter alarm
- + Efficiency test via USB port
- + 4 wheels to allow easy movement of the unit
- + Remote control via RS 232 port
- + Low noise level
- + 4 kits available
- + The fume extraction unit Zero Smog 4V is easy to install and operate. It is designed for use as a small central system. The kits supplied complete with flexible hose, arm and bracket, ready for installation at the workplace. A powerful, maintenance-free turbine provides continuous fume extraction at a maximum air extraction rate of 230 m³/h. With setting constant flow control the adjustable turbine speed avoiding unnecessary waste of suction power and saving energy.

TECHNICAL DATA