



Fume extraction unit Zero Smog 4V

Item No: T0053661299N

Fume extraction unit Zero Smog 4V

KEY FEATURES

- Fume Extraction Unit with a special Gas Filter suitable for applications such as hand soldering, heavy duty and general soldering, gluing, cleaning, filling, fine dust, MEK and VOC
- Mobile fume extraction unit, extracts contaminants at up to 4 workplaces
- Includes F7 fine dust pre-filter and wide band gas filter (50 % active carbon / 50 % Chemisorb)
- Constant Flow Control (CFC) guarantees automatic air flow regulation for each working place independent of the connected workplaces, at the same time avoiding unnecessary waste of suction power and saving energy
- Electronic filter control with optical and acoustic filter alarm enables efficient filter performance monitoring
- A powerful, maintenance-free turbine provides continuous fume extraction
- 🕀 Maximum smoke discharge 230 m³/h
- Electrostatic safety certification

TECHNICAL DATA

Width	325.0 mm
Height	505.0 mm
Length	345.0 mm
Dimensions L x W x H	345.0 x 325.0 x 505.0mm
Capacity (m³/h)	230 m³/h
Compact Filter	Broadband gas filter (50% activated carbon + 50% Chemisorb)
Compatible Nozzle	WX WT
Maximum Blower Vacuum (Pa)	3,800 Pa
Maximum Capacity	1–4 Workstations
Maximum Vacuum	2,700 Pa
Power	275 VA
UPC	037103310774
USB	The USB port can be used to load firmware updates, run efficiency tests and log data. Do not leave the USB medium inserted for longer than 2 minutes. After this time expires, the USB module will switch off automatically.