

## WX2020 Set 230V

Item No: T0053421399N

2-Channel Power Unit, 200 W (255 W)



### KEY FEATURES

- + Power unit WX 2, with 2 channels, 2 soldering irons WXP 120 and 2 safety rests WSR 201
- + Robust touch screen with ESD safe glass
- + Intuitive use with turn-click-wheel with enter key and finger guide.
- + Blue LED backlighting
- + Multilingual menu navigation
- + High functionality
- + No safety rest with Stop & Go function needed thanks to integrated acceleration sensor
- + Optimized precision, better stability by sensor in the soldering iron
- + Specific parameterization of tool by storage medium in hand piece
- + Visual process control via blue LED ring light

## TECHNICAL DATA

|                                     |  |
|-------------------------------------|--|
| Height                              | 135mm  |
| Length                              | 174mm  |
| Dimensions L x W x H                | 174.0 x 154.0 x 135.0mm  |
| Automatic Tool Identification       | Yes  |
| Benchtop Controller                 | Yes  |
| Equipotential Bonding               | Yes  |
| Equipotential Bonding Socket        | Via 3.5mm pawl socket on back of device  |
| ESD Safe                            | Yes  |
| Fuse                                | T2A  |
| Interface                           | 1x USB, 2x RS232, 1x Switching Output  |
| Multilingual Display                | Yes  |
| Number of Channels                  | 2  |
| Power                               | 200 W (255 W)  |
| Temperature Accuracy °C             | ± 9°C  |
| Temperature Accuracy °F             | ± 17°F   |
| Temperature Range (Depends on Tool) | Adjustable from 50°C - 550°C (150°F - 999°F)<br>Adjustable temperature range varies among tools                                    |
| Temperature Range °C                | 100 - 550 °C   |
| Temperature Range °F                | 200 - 999 °C   |
| Temperature Stability °C            | ± 2°C  |
| Temperature Stability °F            | ± 4°F  |
| Traceability                        | Yes  |
| USB                                 | USB interface of firmware updates,<br>parameterization and monitoring USB interface<br>supports all standard USB flash drive types |
| Voltage                             | 230V   |
| Weight (Catalog)                    | 3.45 kg  |
| Product Family                      | WX Line Soldering Stations   |