



ZeroSmog Guard Light 120V

Item No: FT91020299

ZeroSmog Guard Light - Single User
Filtration Unit 60 W, 120 V

ZeroSmog Unit Guard Light, 120 V
1 x main filter (HEPA H13 and
Activated Carbon)
5 x ePM1-75% prefilters

KEY FEATURES

- + Highest level filtration – for cleaner and healthier air**
 - High efficiency particle and gas filtration
 - Odour removal during soldering
 - Powerful blower maintains suction pressure throughout the filter's life
 - High flow rate to collect all the smoke
 - Quiet - lowest noise level on the market – less than 50dB
 - Easy main and pre-filter change
 - Low maintenance
 - Easy-to-reach on/off switch
 - ESD safe
 - Retains Weller Easy-Click 60 Hose system
- + Clean & Healthy Air**
 - Provides superior air quality through high-efficiency filtration of soldering particles and gases with a large filtering surface (H13 HEPA particle filter, activated carbon).
- + Superior Experience**
 - Lowest noise level on the market ensures a healthy, pleasant, and comfortable working environment.
- + Quick and Easy Filter Change**

Ensures user convenience with fast, hassle-free replacements of both, prefilter and main filter.

+ Compact Design

Saves space with a compact, under-the-bench design ideal for single-user use.

+ Powerful Extraction

The robust blower maintains sufficient suction pressure throughout the filter's life, ensuring a high flow rate to capture all smoke effectively.

+ Single User Entry Level Filtration Unit

60 W, 120 V

Highest level filtration – for cleaner and healthier air

High efficiency particle and gas filtration

Odour removal during soldering

Powerful blower maintains suction pressure throughout the filter's life

High flow rate to collect all the smoke

Quiet - lowest noise level on the market – less than 50dB

Easy main and pre-filter change

Low maintainance

Easy-to-reach on/off switch

ESD safe

Retains Weller Easy-Click 60 Hose system

+ ZeroSmog Unit Guard Light, 120 V

1 x main filter (HEPA H13 and Activated Carbon)

5 x ePM1-75% prefilters

TECHNICAL DATA

Dimensions L x W x H	270 x 336 x 435 mm 10.63 x 13.23 x 17.13 in
ESD Safe	Yes
Maximum Capacity	100 (m ³ /h)
Maximum Vacuum	2700 Pa/V
Noise level (distance 1 m) dB(A)	less than 50 dBA
Power	60 W (100-120 V~)
UPC	037103378804
Voltage	100-120V (50/60 Hz)
Weight (Catalog)	9.5 kg
Product Family	Solder Fumes Volume Extraction 1-2 Workstations