

ZeroSmog Guard 2 Kit2 ALFA 120V

Item No: FT91026299
ZeroSmog Guard 2 - Dual User Filtration Unit Kit with Accessories
146 W, 120 V

ZeroSmog Guard 2, 120V,
1 x main filter (HEPA H13 and Activated Carbon + Potassium Permanganate)
5 x Prefilters
2 x ALFA nozzle,
2 x Hose 0F10,
2 x WFV Shut-off Valve
2 x 3m Flexible Hose

KEY FEATURES

- Highest level filtration – for cleaner and healthier air
  High efficiency particle and gas filtration
  Odour removal during soldering
  Powerful blower maintains suction pressure throughout the filter’s life
  High flow rate to collect all the smoke
  Filter condition monitoring to ensure timely filter change
  Bright light bar indicates status of the extraction unit
  Quiet - lowest noise level on the market – less than 55dB
  Easy main and pre-filter change
  Low maintenance
  Easy-to-reach on/off switch
  ESD safe
  Retains Weller Easy-Click 60 Hose system
- Clean & Healthy Air
  Provides superior air quality through high-efficiency filtration of soldering particles and gases with a large filtering surface (H13 HEPA particle filter, activated carbon).
- Superior Experience
  Lowest noise level on the market ensures a healthy, pleasant, and comfortable working environment.
- Quick and Easy Filter Change
  Ensures user convenience with fast, hassle-free replacements of both, prefilter and main filter.
- Compact Design
  Saves space with a compact, under-the-bench design ideal for single-user use.
- Powerful Extraction
  The robust blower maintains sufficient suction pressure throughout the filter's life, ensuring a high flow rate to capture all smoke effectively.
- Maximum Control
  Filter condition monitoring to ensure timely changes, as a full filter cannot clean the air effectively.
- ZeroSmog Guard 2, 120V,
  1 x main filter (HEPA H13 and Activated Carbon + Potassium Permanganate)
  5 x Prefilters
  2 x ALFA nozzle,
  2 x Hose 0F10,
  2 x WFV Shut-off Valve
  2 x 3m Flexible Hose

TECHNICAL DATA

Dimensions L x W x H	270 x 336 x 435 mm 10.63 x 13.23 x 17.13 in
ESD Safe	Yes
Maximum Capacity	200 (m^3/h)
Maximum Vacuum	2250 Pa/V
Noise level (distance 1 m) dB(A)	less than 55 dBA
Power	146 W (100-120 V~)
UPC	037103378934
Voltage	100-120V (50/60 Hz)
Weight (Catalog)	9.5 kg
Product Family	Solder Fumes Volume Extraction 1-2 Workstations