



FOR EVERY PURPOSE.

A NEW REPAIR KIT.

PICO (NANO)/MICRO REWORK KIT, 230 V

ORDER NO: T0053457699



Pico (Nano)/Micro Rework Kit for every purpose. A new soldering kit.

Optimized rework system for all Pico (Nano) and Micro tasks in the electronics, medical, automotive and aerospace industry. The set offers 1 soldering iron with 2 soldering tips from the smallest to bigger soldering application, as well as a desoldering tweezers with pico and micro tips. The tools have the fastest heat-up and recovery times, full tip-to-station process control, best-in-class connectivity, easy-to-use color touch screen and cybersecurity.

+ KEY FEATURES

> SCOPE OF SUPPLY

T0053451699	WXsmart, 2 Channel soldering station, 300 W
T0052923699	WXMPS MS Micro soldering handpiece for pico and micro tips, 40 W, 12 V
T0050109199	RTPS 004 S MS Pico soldering tip, chisel 0,4 x 0,2mm
T0050102399	RTMS 013 S MS Micro soldering tip, chisel 1,3 x 0,4mm
T0051517499N	WSR 200 Safety Rest
T0051321299	WXMTS Tweezers Set with RTWMS 030 KTip and WSR 210 safety rest
T0050115699	RTWPS 002 XTweezers tip, chisel bent 0,2 x 0,1mm
T0053450299	WCTHTip Holder

> COST SAVINGS, 1 IRON - FITS 2 TIP FAMILIES

The kit includes 2 soldering tips, a pico tip and a micro tip. Further a Micro tweezers with 2 tips, a pico tip and a micro tip. Both, the pico tip for very small applications and the micro tip for standard applications fit to just one soldering handle.

> DRIVING FOR EFFICIENCY, FAST HEAT-UP TIMES

The new Pico (Nano)/Micro Soldering and desoldering tools have the fastest heat-up and recovery times of less than 3 seconds. Excellent heat transfer and recovery time during the soldering process for a high performance and continuous workflow. The short tip-to-grip distance provides maximum precision during the soldering process.

> FULL PROCESS CONTROL

Smart tips with a unique individual serial number, smart tools

for data parameter storage and an intelligent station ensure full process control and full traceability of calibration history.

> INDIVIDUAL AND REPEATABLE SOLDERING PROCESSES

Up to 10 parameter settings can be customized and stored in the iron, including standby temperatures and auto-off times.

> ALL-IN-ONE STATION

All-in-one Wxsmart solder station for all your pico and micro application. The station is equipped with 300 W, 2 soldering channels. A total of 12 tools can be connected to Wxsmart.

> PROTECTION AGAINST CYBER ATTACKS

TLS encryption and two-factor authentication (2FA), including Weller's built-in certificate upload mechanism that provides the soldering station with a customer verification-certificate, and protected software updates

> HIGHER QUALITY OUTPUT

Managing your entire soldering process, from tip to station, has never been easier or more productive with the first all-in-one Wxsmart Hand Soldering platform. With Total Process Control, the Wxsmart offers maximum connectivity and traceability at the highest quality. The platform fully supports supports all IoT standards. It is the first hand soldering station with cybersecurity to prevent costly downtime.

> ESD Safe

The Wxsmart Station and all the connected tools are fully ESD safe.





FOR EVERY PURPOSE. A NEW REPAIR KIT. PICO (NANO)/MICRO REWORK KIT, 230 V

ORDER NO: T0053457699



TECHNICAL DATA

TECHNICAL DATA SOLDERING STATION WXsmart

Dimensions L x W x H 173 mm x 153 mm x 142 mm / 6,81 inch x 6,02 inch x 5,59 inch
Weight 4,5 kg
Mains supply voltage 100V AC / 50/60 Hz 120V AC / 60 Hz 230V AC / 50/60 Hz
Power consumption 300W
Safety class I, Supply unit / III, Soldering tool
Fuse 100V / T6,3A 120V / T5A 230V / T3,15A
Temperature range 100 - 450°C (550°F) Tool dependent 200 - 850°F (950°F)
Temperature accuracy ± 9 °C / ± 17 °F
Temperature stability ± 2 °C / ± 4 °F
Subject to technical alterations and amendments.

TECHNICAL DATA WXMTS Tweezers

Temperature Range 100 - 450°C / 200 - 850°F
Power Consumption 80 W
Mains Supply Voltage 12 V / AC
Heat up Time (50°C - 350°C) (120°F - 660°F) 5 sec
Military Standard According to Military Standard, Mil-Spec compliant and fully compliant to IPC industry standards (IPC - TM-650 2.5.33 Measurement of Electrical Overstress from Soldering Hand Tools)
ESD safe 
Fits to WXsmart Soldering Station
Tip Family RTWMS & RTWPS
Subject to technical alterations and amendments.

TECHNICAL DATA SOLDERING IRON WXMPS MS (PICO/MICRO)

Temperature range °C: 100 - 450
Temperature range °F: 200 - 850
Power consumption: 40 W
Mains supply voltage: 12V / AC
Heat-up time: 3 s (50°C to 350°C / 120°F to 660°F)
Tip type series: RTMS MS / RTPS MS
Safety rest: WSR 208
Supply unit: WX Smart Station
Subject to technical alterations and amendments.



Further information
www.weller-tools.com/wxsmart