

Safety Data Sheet according to
Regulation (EC) No. 1907/2006
(REACH)Weller Pyropen Refill, 75 ml / 42gPrint date29.10.2015Revision date29.10.2015Version5.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification on the label/Trade name

label designation/Name of product

Pyropen Refill

Other means of identification

SDS-01

Trade name/designation Weller Pyropen Refill, 75 ml / 42g Article no. (user): No. T005 16 160 99 / 49

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Identified uses:

burning gas / Brenngas / gaz combustible / gas combustibile / O gás combustivel / brandstof gas / bränslegas / braendselsgas / brenngass / polttoaine kaasu / paliwo gazowe / küttegaasi / deggazes / Kuro dujos / vykurovaci plyn / gorivo plin / gaz

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Weller Tools GmbH Carl-Benz-Straße 2 Germany-74354 Besigheim P.O. Box: Telephone: +49 7143 580-0 Telefax: +49 7143 580-108 E-mail: info@weller-tools.com Dept. responsible for information: environmental department Information telephone: +49 7143 580-101 Information telefax: +49 7143 580-108 Emergency telephone number: GIZ Mainz +49 6131 - 19240 (german, english, french)

1.4 Emergency telephone number

No data available

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards:

Physical hazards Flam. Gas 1 hazard statements for physical hazards H220 Extremely flammable gas. hazard statements for physical hazards H280 Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms



GHS02 Signal word Danger

Hazard Statements:

Hazard statements for physical hazards:

H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated.

Precautionary Statements:

General:

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



>=10 - <=25 %

>=25 - <=50 %

>=50 - <=100 %

P251 Do not pierce or burn, even after use.

Response:

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

Storage:

P403 Store in a well-ventilated place.

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.

Special rules for supplemental label elements for certain mixtures

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Special rules on packaging

Tactile warning according to EN/ISO 11683.

2.3 Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.1/3.2 Mixture related information

Description

mixture / Gemisch / mélange / mezcla / mistura / mengsel / Blandning / Blanding / seos / mieszanina / segu / maisijums / misinys / zmes / mesanica / karisim

Hazardous ingredients

propane

CAS 74-98-6 EC 200-827-9 INDEX 601-003-00-5 Flam. Gas 1, H220

isobutane

CAS 75-28-5 EC 200-857-2 INDEX 601-004-00-0 Flam. Gas 1, H220

butane

CAS 106-97-8 EC 203-448-7 INDEX 601-004-00-0 Flam. Gas 1, H220

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Following inhalation

Provide fresh air. In case of irritation of the respiratory tract seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water and soap.

After eye contact

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

4.2 Most important symptoms and effects, both acute and delayed

No data available

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Additional information

In case of fire and/or explosion do not breathe fumes. Use water spray/stream to protect personnel and to cool endangered containers.

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Extinguishing powder. Atomized water. alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.



Safety Data Sheet according to
Regulation (EC) No. 1907/2006
(REACH)Weller Pyropen Refill, 75 ml / 42gPrint date29.10.2015Revision date29.10.2015Version5.2

No data avail	able			
5.3 Advice No data avail	for firefighters able			
ECTION 6: A	ccidental release measure	es		
6.1 Person	al precautions, protective	e equipment and emerged	gency procedu	ires
For non-en	nergency personnel			
	recautions			
-	uate ventilation. Remove all sou	rces of ignition.		
No special en	nmental precautions vironmental measures are neces	•		
No data avail		nment and cleaning up)	
6.4 Refere No data avail	nce to other sections able			
	landling and storage			
7.1 Precau	itions for safe handling			
Protective				
	a safe handling on naked flames or any incande	escent material. After use re	place the closing	cap immediately.
	to prevent fire rom sources of ignition - No smol void bumps, friction and impact.	king. Keep away from heat	sources (e.g. hot	surfaces), sparks and open flames. Hand
7.2 Conditi	ions for safe storage, inclu	uding any incompatibi	ities	
Hints on jo Materials t	oint storage	uding any incompatibi	ities	
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature po- to end use(s)	litions ursting. Keep in a cool, well		
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bust: iation/sunlight. at temperatures above naximum storage temperature po ic end use(s) able	litions ursting. Keep in a cool, well ermitted:		
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature pu- to end use(s) able xposure controls/persona	litions ursting. Keep in a cool, well ermitted:		
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of be ist: iation/sunlight. at temperatures above naximum storage temperature per ic end use(s) able xposure controls/persona I parameters	litions ursting. Keep in a cool, well ermitted:		
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature pu- to end use(s) able xposure controls/persona	litions ursting. Keep in a cool, well ermitted:		remark
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro Occupation	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bust: iation/sunlight. at temperatures above naximum storage temperature point to end use(s) able xposure controls/personal l parameters nal exposure limit values	litions ursting. Keep in a cool, well ermitted: al protection	-ventilated place. STV	remark
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro Occupation CAS No.	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature pu- to end use(s) able xposure controls/personal l parameters nal exposure limit values Substance name	litions ursting. Keep in a cool, well ermitted: al protection	-ventilated place. STV	remark
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro Occupation CAS No. 106-97-8	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of be ist: iation/sunlight. at temperatures above naximum storage temperature per ic end use(s) able xposure controls/personal l parameters nal exposure limit values Substance name Butane m occupational exposure limit value	litions ursting. Keep in a cool, well ermitted: al protection LTV 1450 mg/m ³ 600 ppm	-ventilated place. STV	remark 50 ppm
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro Occupation CAS No. 106-97-8 LTV = long-tern STV = short-te	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature pu- ic end use(s) able xposure controls/personal l parameters nal exposure limit values Substance name Butane m occupational exposure limit value	litions ursting. Keep in a cool, well ermitted: al protection LTV 1450 mg/m ³ 600 ppm	-ventilated place. STV	remark 50 ppm
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro Occupation CAS No. 106-97-8 LTV = long-tern STV = short-te 8.2 Exposu	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature pu- to end use(s) able xposure controls/personal l parameters nal exposure limit values Substance name Butane m occupational exposure limit value ure controls	litions ursting. Keep in a cool, well ermitted: al protection LTV 1450 mg/m ³ 600 ppm	-ventilated place. STV	remark 50 ppm
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro Occupation CAS No. 106-97-8 LTV = long-teri STV = short-te 8.2 Exposu Appropriat	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature pu- to end use(s) lable xposure controls/personal l parameters nal exposure limit values Substance name Butane m occupational exposure limit value irm occupational exposure limit value irm occupational exposure limit value irm occupational exposure limit value irm occupational exposure limit value	litions ursting. Keep in a cool, well ermitted: al protection LTV 1450 mg/m ³ 600 ppm	-ventilated place. STV	remark 50 ppm
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro Occupation CAS No. 106-97-8 LTV = long-teri STV = short-te 8.2 Exposu Appropriat Technical i	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature pu- to end use(s) able xposure controls/personal l parameters nal exposure limit values Substance name Butane m occupational exposure limit value ure controls	litions ursting. Keep in a cool, well ermitted: al protection LTV 1450 mg/m ³ 600 ppm	-ventilated place. STV	remark 50 ppm
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro Occupation CAS No. 106-97-8 LTV = long-term STV = short-te 8.2 Exposu Appropriat Technical I refer to chapt	bint storage co avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature pu- ic end use(s) able xposure controls/personal l parameters nal exposure limit values Substance name Butane m occupational exposure limit value rm occupational exposure limit value ure controls te engineering controls measures to prevent expo ter 7. No further action is necess protection equipment	litions ursting. Keep in a cool, well ermitted: al protection LTV 1450 mg/m ³ 600 ppm	-ventilated place. STV	remark 50 ppm
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro Occupation CAS No. 106-97-8 LTV = long-tern STV = short-te 8.2 Exposu Appropriat Technical p refer to chapt	bint storage to avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature pu- ic end use(s) able xposure controls/personal l parameters nal exposure limit values Substance name Butane m occupational exposure limit value irm occupational exposure limit value irm occupational exposure limit value irm occupational exposure limit value irm controls te engineering controls measures to prevent expo ter 7. No further action is necess	litions ursting. Keep in a cool, well ermitted: al protection LTV 1450 mg/m ³ 600 ppm	-ventilated place. STV 1810 mg/m ³ 75	remark 50 ppm Great Britain (UK)
Hints on jo Materials t Do not store Oxidizing age Further inf Heating cause Protect again heat. UV-radi Do not store Short-term m 7.3 Specifi No data avail ECTION 8: E 8.1 Contro Occupation CAS No. 106-97-8 LTV = long-tern STV = short-te 8.2 Exposu Appropriat Technical p Respirator With correct a	bint storage co avoid together with: ents. formation on storage cond es rise in pressure with risk of bu- ist: iation/sunlight. at temperatures above naximum storage temperature pu- ic end use(s) able xposure controls/personal l parameters nal exposure limit values Substance name Butane m occupational exposure limit value rm occupational exposure limit value tre controls te engineering controls measures to prevent expo ter 7. No further action is necess protection equipment ry protection	litions ursting. Keep in a cool, well ermitted: al protection LTV 1450 mg/m ³ 600 ppm	-ventilated place. STV 1810 mg/m ³ 75	remark 50 ppm Great Britain (UK)



SECTION 9: Physical and chemical properties 9.1 Information on basic physical and chemical properties Appearance Physical state Aerosol

Colour colourless

Odour

characteristic

		parameter	Method - source - remark
рН			No data available
Melting point/freezing point			No data available
Initial boiling point and boiling range	-44 °C		
Flash point (°C)	-97 °C		
Evaporation rate			No data available
Flammable solids			No data available
Flammable aerosols			No data available
Upper explosion limit (Vol-%)	10,9 Vol-%		
Lower explosion limit (Vol-%)	1,5 Vol-%		
Vapour pressure			No data available
Density	ca.0,56 g/cm ³	at °C: 20 °C	
Vapour density			No data available
Fat solubility (g/L)			No data available
Water solubility (g/L)			not miscible
Soluble (g/L) in			No data available
Partition coefficient: n-octanol/water			No data available
Auto-ignition temperature			No data available
Auto-ignition temperature	365 °C		
Decomposition temperature			No data available
Explosives			No data available
Oxidising gases			No data available
Oxidising liquids			No data available
Oxidising solids			No data available
9.2 Other safety information Solvent content (%) 0 % remark VOC (EU) 100%			
SECTION 10: Stability and react	tivity		
10.1 Reactivity No data available			
10.2 Chemical stability No data available			
10.3 Possibility of hazardous No data available	s reactions		
10.4 Conditions to avoid In case of warming: Danger of bursting container. >50°C			



Safety Data Sheet according to
Regulation (EC) No. 1907/2006
(REACH)Weller Pyropen Refill, 75 ml / 42gPrint date29.10.2015Revision date29.10.2015Version5.2

10.5 Incompatible materials No data available 10.6 Hazardous decomposition products No data available

SECTION 11: Toxicological information

Toxicokinetics, metabolism and distribution

Non-human toxikological data

remark

There are no data available on the preparation/mixture itself.

11.1 Information on toxicological effects

skin corrosion/irritation

Skin corrosion

Result / evaluation Not an irritant.

Eye damage/irritation

Result / evaluation

Not an irritant.

SECTION 12: Ecological information

12.1 Toxicity

Additional ecotoxicological information

Additional information

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see chapter 3).

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential No data available

12.4 Mobility in soil No data available

12.5 Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Appropriate disposal / Product

Appropriate disposal/Product:

Waste disposal according to official state regulations.

Appropriate disposal / Package

Contaminated packaging:

Completely emptied packings can be re-cycled.

Waste code packaging 160500 Special monitoring requiring wastes: No

Waste name

gases in pressure containers and discarded chemicals Waste code packaging 160000

Special monitoring requiring wastes: No

Waste name

WASTES NOT OTHERWISE SPECIFIED IN THE LIST

Waste code packaging 160505

Special monitoring requiring wastes: No

Waste name

gases in pressure containers other than those mentioned in 16 05 04

SECTION 14: Transport information

-	-	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
	14.1 UN-No.	2037	2037	2037

Weller

Safety Data Sheet according to
Regulation (EC) No. 1907/2006
(REACH)Weller Pyropen Refill, 75 ml / 42gPrint date29.10.2015Revision date29.10.2015Version5.2

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.2 Proper Shipping Name	RECEPTACLES, SMALL, CONTAINING GAS	RECEPTACLES, SMALL, CONTAINING GAS	Receptacles, small, containing gas
14.3 Class(es)	2	2.1	2.1
14.4 Packing group			
14.5 ENVIRONMENTALLY HAZARDOUS	No	No	No
14.6 Special precautions for user	not applicable	not applicable	not applicable
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	not applicable	not applicable	not applicable

Additional information - Land transport (ADR/RID) Hazard label(s) 2.1

Limited quantity (LQ)	1 L
tunnel restriction code	D
transport category	2
Additional information - Sea tra	nsport (IMDG)
Marine pollutant	No
remark	EMS-No.: F-D,S-U
Additional information - Air tran	nsport (ICAO-TI / IATA-DGR)
Limited quantity (10)	1

Limited quantity (LQ) remark - Land transport (ADR/RID)

Transport as "limited quantity" according to chapter 3.4 ADR/RID

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU legislation

Authorisations and/or restrictions on use

Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU)

To follow:

Aerosol directive (75/324/EEC)

15.2 Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Relevant R-, H- and EUH-phrases (Number and full text)

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Key literature references and sources for data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.