



The can-do **WT** soldering stations.

High flexibility for versatile applications - **WT** Line

They were made for each other. Weller's WT Line compact, user-friendly suite of soldering and rework products all fit together nicely to give you the space you crave on your workbench.

Stackable, smart power units. Interlocking, reversible safety rests. Convenient and safe tip storage. A sleek 90 watt pencil. Microsoldering capacity. And backwards compatibility affording you over 1,000 tip/tool combinations.

Technical Data		WT 1	WT 1H	WT 2M	WTHA 1
Dimensions	L x W x H	150 x 130 x 101 mm 5.91 x 5.12 x 3.98 in			210 x 160 x 125 mm 8.30 x 6.30 x 4.90 in
Fuse	230V (mA) 120V (A)	T500 T1	T800 T1,6	T0,8 T1,6	T4 A T8 A
Weight		1.9 kg	1.9 kg	2,92 kg	3.0 kg
Mains supply		230V / 50 Hz, 120V / 60 Hz			
Power consumption		90 W	150 W		900 W
Safety class		I. Antistatic housing		III. Soldering tool	I. Antistatic housing
ESD safe		Yes			
Temperature range l/min 5 - 60		50 °C – 450 °C / 550 °C			50 °C – 600 °C
Temperature accuracy		± 9 °C / ± 17 °F			± 30 °C / ± 54 °F
Temperature stability		± 2 °C / ± 4 °F			
Air flow		–			100 l (expanded hot air)

Weller[®]

weller-tools.com