

WAD101N Kit 120V

Item No: WAD101N

Hot air station, 1 channel 120 V / 60 Hz



KEY FEATURES

- + Optional WCB1 - T0053118299 programming module provides temperature lock-out, set back, ° F to ° C conversion, factory reset functions
- + Requires clean, filtered compressed air supply of 58 - 87 PSI

TECHNICAL DATA

Length	6.8 in
Dimensions L x W x H	175.0 x 135.0 x 102.0mm
Air Consumption	10 l/min
Capacity (l/min)	10 l/min
Compressed Air Connection (Outer Diameter)	6.0mm
Compressed Air Connection Accessory	Oil free, dry compressed air
Compressed Air Supply (kPa/bar)	400 kPa / 4 bar
Equipotential Bonding Socket	Via 3.5mm jack bush (initial state-hard-grounded)
Fuse	T10A
Hot Air (picto)	Yes
Inert Gas Function	The inlet pressure is set permanently to 200 kPa by a pressure regulator. The pressure regulator must not be adjusted.
Maximum Hot Air Flow Rate l/min (Depends on Tool)	0 - 10 l/min
Number of Channels	1
Operating Pressure	4 bar 58 psi
Power	105 W
Temperature Accuracy °C	± 9°C, ± 30°C
Temperature Accuracy °F	± 17°F, ± 50°F
Temperature Range °C	50 - 450 °C (550 °C)
Temperature Range °F	122 - 842 °F (999 °F)
Temperature Stability °C	± 2°C
Temperature Stability °F	± 5°F
UPC	037103304100
Voltage	120V (60 Hz)
Weight (Catalog)	2.40 kg
Product Family	Rework, Hot Air, Desoldering Stations