



## **2-Channel Hot-Air Station, 200 W (255 W)**

Item No: WXA2010N

2-Channel Hot-Air Station, 200 W  
(255 W)

### **KEY FEATURES**

- + Power unit, 2 channels with hot air iron WXHAP 200
- + Best set for hot air tasks
- + Simultaneous operation of 2 soldering tools
- + For operation with external compressed air

# TECHNICAL DATA

|                                                   |                                                                                                                              |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Dimensions L x W x H                              | 174.0 x 154.0 x 135.0mm                                                                                                      |
| Air Consumption                                   | 20 l/min                                                                                                                     |
| Capacity (l/min)                                  | 20 l/min                                                                                                                     |
| Compressed Air Connection (Outer Diameter)        | 0.23 in                                                                                                                      |
| Compressed Air Connection Accessory               | Oil free, dry compressed air                                                                                                 |
| Equipotential Bonding Socket                      | Via 3.5mm Pawl Socket on Back of Device                                                                                      |
| ESD Safe                                          | Yes                                                                                                                          |
| Fuse                                              | T2A                                                                                                                          |
| Hot Air (picto)                                   | Yes                                                                                                                          |
| Interface                                         | 1x USB, 2x RS232, 1x Switching Output                                                                                        |
| Maximum Hot Air Flow Rate l/min (Depends on Tool) | 15 l/min                                                                                                                     |
| Number of Channels                                | 2                                                                                                                            |
| Operating Pressure                                | 4 - 6 bar 54 - 87 psi                                                                                                        |
| Power                                             | 200 W (255 W)                                                                                                                |
| Temperature Accuracy °C                           | ± 9 °C                                                                                                                       |
| Temperature Accuracy °F                           | ±9 °C                                                                                                                        |
| Temperature Accuracy for Hot Air                  | ±30 °C                                                                                                                       |
| Temperature Range °C                              | 93 - 537 °C                                                                                                                  |
| Temperature Range °F                              | 199 - 998 °F                                                                                                                 |
| Temperature Stability °C                          | ±2 °C                                                                                                                        |
| Temperature Stability °F                          | ±2 °C                                                                                                                        |
| Tip Type                                          | WX                                                                                                                           |
| UPC                                               | 037103304247                                                                                                                 |
| USB                                               | USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types |
| Voltage                                           | 110 V                                                                                                                        |