



WT2M 120V

Item No: WT2M

2-Channel Power Unit, 150 W

KEY FEATURES

- + Serving 2 users at once (with intelligent power sharing)
- + High performance and functionality - Compatible with Weller's microsoldering cartridge tip tools, plus many existing passive tip tools
- + Intuitive use thanks to clear menu structure
- + Reduced footprint thanks to stackability
- + Housing cover useable as storage
- + Lock function

Compact. Powerful. Versatile.



TECHNICAL DATA

Length	5.8 in
Dimensions L x W x H	5.91 x 5.12 x 3.98 In
Automatic Tool Identification	Yes
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3.5mm pawl socket on front of device
ESD Safe	Yes
Fuse	T1.6A
Interface	RS232 / One Switching Output
Number of Channels	2
Overcurrent Release	T40/B
Power	150 W
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range °C	50 - 450 °C (550 °C)
Temperature Range °F	150 - 850 °F (950 °F)
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
Tip Type	WT
UPC	037103326911
Voltage	120V, 24V
Weight (Catalog)	3.10 kg
Product Family	WT Line Soldering Stations