



WT2M

Item No: WT2M 2-Channel Power Unit, 150 W

KEY FEATURES

- Serving 2 users at once (with intelligent power sharing)
- High performance and functionality Compatible with Weller's microsoldering cartridge tip tools, plus many existing passive tip tools
- Intuitive use thanks to clear menu structure
- Reduced footprint thanks to stackability
- Housing cover useable as storage
- Lock function

Compact. Powerful. Versatile.



TECHNICAL DATA

Dimensions L x W x H	149.0 x 138.0 x 101.0mm
Automatic Tool Identification	Yes
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3.5mm Pawl Socket on Front of Device
ESD Safe	Yes
Fuse	T1.6A
Interface	RS232 / One Switching Output
Number of Channels	2
Overcurrent Release	T40/B
Power	150 W
Temperature Accuracy °C	±9 °C
Temperature Accuracy °F	±17 °F
Temperature Range °C	50 - 450 °C (550 °C)
Temperature Range °F	150 - 850 °F (950 °F)
Temperature Stability °C	±2 °C
Temperature Stability °F	±4 °F
Tip Type	WT
UPC	037103326911
Voltage	120 V / 24 V
Weight (Catalog)	3.10 kg