



2-Channel Power Unit, 200 W (255 W)

Item No: WXA2N

2-Channel Power Unit, 200 W (255 W)

KEY FEATURES

- + For operation with external compressed air
- + Compatible with all WX series tools
- + When using WXHAP200 hot air pen, only WXMP-MS or WXMP series tools can be used at the same time
- + Benchtop controller for WHP1000/WHP3000 heating plates
- + Benchtop controller for use as Zero Smog 4V/6V filter unit
- + Air flow: 0 - 20 l/min
- + Required compressed air supply: 400 - 600 kPA (58 - 87 psi); oil-free, dry compressed air

TECHNICAL DATA

Dimensions L x W x H	6.6 x 5.9 x 5.1 in
Air Consumption	20 l/min
Automatic Tool Identification	Yes
Benchtop Controller	Yes
Capacity (l/min)	20 l/min
Compressed Air Connection (Outer Diameter)	0.23 in
Compressed Air Connection Accessory	Oil free, dry compressed air
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3.5mm Pawl Socket on Back of Device
ESD Safe	Yes
Fuse	T2A
Hot Air (picto)	Yes
Interface	1x USB, 2x RS232, 1x Switching Output
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Multilingual Display	Yes
Number of Channels	2
Operating Pressure	4 - 6 bar 54 - 87 psi
Power	200 W (255 W)
Temperature Accuracy °C	± 9 °C
Temperature Accuracy °F	± 17 °F
Temperature Accuracy for Hot Air	± 54 °F
Temperature Range °C	100 - 550 °C
Temperature Range °F	200 - 999 °F
Temperature Stability °C	±2 °C
Temperature Stability °F	±4 °F
Tip Type	WX
Traceability	Yes
UPC	037103312389
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types

Vacuum	0.6 bar (60 kPA) (8.7 psi)
Voltage	120 V