



ZERO SMOG TL KIT 1 w.extra FilterSet

Item No: ZEROSMOGTLKIT1NP
Fume extraction unit Zero Smog TL

The Zero Smog TL fume extraction system is specifically designed for continuous operation in industrial environments. With its small footprint, it is perfect for use as a small central system and purifies air up to 2 workplaces. The maintenance free brushless EC turbine provides continuous fume extraction.

KEY FEATURES

- Fume extraction system purifies air up to 2 workplaces, included funnel nozzle for applications where a larger area needs to be covered and the funnel nozzle can be placed directly on the work bench
- Equipped with a F7 fine dust pre-filter and a main filter consisting of: HEPA H13 Particle filter and wide band gas filter (1,8kg granular activated carbon media)
- Visual and audible filter-full alarm
- 1.8kg of granular activated carbon filter media, for effective gas filtration
- Quiet operation
- Easily operated and easy filter replacement
- Variable speed setting
- For connection to a WX / WT station a T0058768767 WT Hub is needed
- en Exceptionally long service life due to maintenance free brushless EC turbine

TECHNICAL DATA

Dimensions L x W x H	335.0 x 330.0 x 445.0mm
Compact Filter	H13 particulate filter and active carbon particulate filter
Fuse	T1.25A
Maximum Blower Vacuum (Pa)	3,000 Pa
Maximum Capacity	1–2 Workstations
Power	120 W
UPC	037103336880
Weight (Catalog)	9.00 kg