




## RTWPS 001 C MS


Item No: T0050115499




Production within the electronics, medical technology and aerospace industries is moving faster than ever before, as components have become smaller and more sensitive. With a new generation of RTWPS Pico Tips, Weller meets these increasing demands with its Pico tweezers desoldering tips which provide an optimized heat transfer with 2 x 40W maximum power, 12V performance for very small to small components (XS to S). Lock functions make the soldering processes repeatable and transparent. Weller offers a selection of smallest smart soldering tips for pico applications. The parallel sliding block allows for increased productivity with the pre-adjusted ready-to-use pairwise tip design.

## KEY FEATURES

-  High-Performance / High-Productivity
  - Extremely short heat-up time: 5 sec.
  - Quick response time
-  Highest Precision
  - Maximum precision during the soldering process with short tip-to-grip distance and optimized tip design.
  - Precise positioning ensured with unique parallel sliding block guide.
  - No alignment necessary after tip change with pairwise design
  - Adjustability functions with Allen key: 1.5mm possible if needed ( $\pm 80^\circ$  rotation angle adjustment + vertical length adjustment of  $\pm 1.2\text{mm}$ )
  - Desoldering Tweezers Tips allow Automatic Tip-Offset
-  Fastest Tweezers Tip Change

Active Tip Cartridge System allows for easy exchange of soldering tip even with a hot desoldering tweezer, all without needing an extra tool or further adjustment
-  Ergonomics

Improved comfort and safe handling with new ergonomic soft grips
-  Unique intelligent Tweezers tips

For use with WXsmart Tweezers WXMTS only

  - Automatic Smart Tweezers Tip Identification
  - Full Traceability with Tweezers Tip ID Number and Integrated Data Storage
  - Accurate Data Results with Tip-Offset Function
  - Full Process Control with Tip Lock Function

# TECHNICAL DATA

Approximate Heating Time (50–350 °C/120–660 °F)	5 sec
ESD Safe	Yes
Power Consumption	2 x 40 W
Temperature Range °C	100 - 450
Temperature Range °F	200 - 850
Tip Range	RTWPS
Tip Shape	conical
Tip Width	0.1
UPC	037103371348
Voltage	12 V / AC
Works With	WXMTS and WTMT
Product Family	SMART RTWPS Desoldering Tweezers Tips