



RTWPS 002 S X

Item No: T0050115699 Pair of Pico Soldering and Desoldering Tips, 2 x 40 W, 12 V

Production within the electronics, medical technology and aerospace industries is moving faster than ever before, as components have become smaller and more sensitive. With a new generation of RTWPS Pico Tips, Weller meets these increasing demands with its Pico tweezers desoldering tips which provide an optimized heat transfer with 2 x 40W maximum power, 12V performance for very small to small components (XS to S). Lock functions make the soldering processes repeatable and transparent. Weller offers a selection of smallest smart soldering tips for pico applications. The parallel sliding block allows for increased productivity with the pre-adjusted ready-to-use pairwise tip design.

KEY FEATURES

- High-Performance / High-Productivity
 - Extremely short heat-up time: 5 sec.
 - Quick response time

🕂 Highest Precision

- Maximum precision during the soldering process with short tip-to-grip distance and optimized tip design.

- Precise positioning ensured with unique parallel sliding block guide.
- No alignment necessary after tip change with pairwise design
- Adjustability functions with Allen key: 1.5mm possible if needed

 $(\pm 80^{\circ} \text{ rotation angle adjustment} + \text{vertical length adjustment of } \pm 1.2 \text{mm})$

- Desoldering Tweezers Tips allow Automatic Tip-Offset
- 🕒 Fastest Tweezers Tip Change

Active Tip Cartridge System allows for easy exchange of soldering tip even with a hot desoldering tweezer, all without needing an extra tool or further adjustment

Ergonomics Improved comfort and cafe bandling with now organomic

Improved comfort and safe handling with new ergonomic soft grips

Unique intelligent Tweezers tips For use with WXsmart Tweezers WXMTS only

- Automatic Smart Tweezers Tip Identification
- Full Traceability with Tweezers Tip ID Number and Integrated Data Storage
- Accurate Data Results with Tip-Offset Function
- Full Process Control with Tip Lock Function

TECHNICAL DATA

Length	0.6 in
Approximate Heating Time (50–350 °C/120–660 °F)	5 sec
ESD Safe	Yes
Power Consumption	2 x 40 W
Temperature Range °C	100 - 450
Temperature Range °F	200 - 850
Tip Range	RTWPS
Tip Shape	Chisel
Tip Width	0.2
UPC	037103371362
Voltage	12 VAC
Works With	WXMTS and WTMT
Product Family	SMART RTWPS Desoldering Tweezers Tips