

WR 3M

Item No: T0053366699N

3-Channel Power Unit, 360 W (400 W)



KEY FEATURES

- + 3 independent tool channels
- + Simultaneous operation of up to 3 soldering tools
- + Automatic tool detection
- + Own vacuum channel for pick-up

TECHNICAL DATA

Length	11 in
Dimensions L x W x H	280.0 x 240.0 x 103.0mm
Capacity (l/min)	18 l/min
Desoldering	Yes
Equipotential Bonding Socket	Via 3.5mm Pawl Socket on Back of Device (Hard-Grounded)
ESD Safe	Yes
Hot Air (picto)	Yes
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	3
Overcurrent Release	2 A
Power	360 W (400 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range (Depends on Tool)	Temperature control of channels Soldering and desoldering iron stepless 50 °C - 550 °C (150 °F - 999 °F) Controllable temperature range depends on the tool
Temperature Range °C	93 - 454 °C
Temperature Range °F	200 - 850 °F
Tip Type	WT
UPC	037103305473
USB	Yes
Voltage	230 V
Weight (Catalog)	7.30 kg
Product Family	Rework, Hot Air, Desoldering Stations