

WR3M 230V

Item No: T0053366699N
3-Channel Power Unit, 360 W (400 W)

KEY FEATURES

- 3 independent tool channels
- Simultaneous operation of up to 3 soldering tools
- Automatic tool detection
- Own vacuum channel for pick-up

TECHNICAL DATA

Length	11 in
Dimensions L x W x H	280.0 x 240.0 x 103.0mm
Capacity (l/min)	18 l/min
Desoldering	Yes
Equipotential Bonding Socket	Via 3.5mm pawl socket on back of device (hard-grounded)
ESD Safe	Yes
Hot Air (picto)	Yes
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	3
Overcurrent Release	2 A
Power	360 W (400 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range (Depends on Tool)	Temperature control of channels Soldering and desoldering iron stepless 50 °C – 550 °C (150 °F – 999 °F) Controllable temperature range depends on the tool
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
Tip Type	WT
UPC	037103305473
USB	Yes
Voltage	230V
Weight (Catalog)	7.30 kg
Product Family	Rework, Hot Air, Desoldering Stations