

WR2000D Set 230V

Item No: T0053379699N

Desoldering station, 2 channels, 250 W



KEY FEATURES

- + Power unit WR 2, 2 channels with desoldering iron DSX 80 and safety rest WSR 209
- + Repair kit for soldering and desoldering

TECHNICAL DATA

Length	10.7 in
Dimensions L x W x H	273.0 x 235.0 x 102.0mm
Automatic Tool Identification	Yes
Capacity (l/min)	18 l/min
Desoldering	Yes
Equipotential Bonding Socket	Via 3.5mm jack bush (initial state-hard-grounded)
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001D
Maximum Hot Air Flow Rate l/min (Depends on Tool)	10 l/min
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	2
Overcurrent Release	1,6 A
Power	300 W
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Accuracy for Hot Air	± 30°C, ± 54°F
Temperature Range (Depends on Tool)	Soldering and desoldering tool, continuously variable from 50 °C - 550 °C (150 °F - 999 °F) Controllable temperature range is tooldependent
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
UPC	037103305510
Voltage	230V
Weight (Catalog)	6.70 kg
Product Family	Rework, Hot Air, Desoldering Stations