

## WR2002 Set 230V

Item No: T0053380699N
2-Channel Rework Station Set, 200 W (300 W)

## KEY FEATURES

- Power unit WR 2, 2 channels with soldering iron WP 80, desoldering iron DSX 80
- Small repair set for all rework applications
- Simultaneous operation of up to 2 soldering tools (hot air and desoldering iron at the same time is not possible)

## TECHNICAL DATA

| | |
|---|---|
| Length | 10.7 in |
| Dimensions L x W x H | 273.0 x 235.0 x 102.0mm |
| Automatic Tool Identification | Yes |
| Capacity (l/min) | 18 l/min |
| Desoldering | Yes |
| Equipotential Bonding Socket | Via 3.5mm jack bush (initial state-hard-grounded) |
| ESD Safe | Yes |
| Hot Air (picto) | Yes |
| IPC Compliant | (Tip to Ground) Corresponds to IPC-J-001D |
| Maximum Hot Air Flow Rate l/min (Depends on Tool) | 10 l/min |
| Noise level (distance 1 m) dB(A) | 0.7 bar |
| Number of Channels | 2 |
| Overcurrent Release | 1,6 A |
| Power | 250 W (300 W) |
| Temperature Accuracy °C | ± 9°C |
| Temperature Accuracy °F | ± 17°F |
| Temperature Accuracy for Hot Air | ± 30°C, ± 54°F |
| Temperature Stability °C | ± 2°C |
| Temperature Stability °F | ± 4°F |
| UPC | 037103305527 |
| Vacuum | 0,7 bar |
| Voltage | 230V |
| Weight (Catalog) | 6.70 kg |
| Product Family | Rework, Hot Air, Desoldering Stations |