



WR2 120V

Item No: WR2N

2-Channel Power Unit, 200 W (300 W)

KEY FEATURES

- + Digital Self-Contained Multi-Channel Rework Station - 120 V / 300 W
- + 2 Independent tool channels with automatic tool recognition

TECHNICAL DATA

Length	11 in
Dimensions L x W x H	280.0 x 240.0 x 103.0mm
Automatic Tool Identification	Yes
Capacity (l/min)	18 l/min
Desoldering	Yes
Equipotential Bonding Socket	Via 3.5mm jack bush (initial state-hard-grounded)
ESD Safe	Yes
Hot Air (picto)	Yes
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001
Maximum Hot Air Flow Rate l/min (Depends on Tool)	10 l/min
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	2
Overcurrent Release	1.6 A
Power	250 W (300 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Accuracy for Hot Air	± 30°C, ± 54°F
Temperature Range (Depends on Tool)	Temperature control of channelsSoldering and desoldering iron stepless 50 °C – 550 °C (150 °F – 999 °F)Controllable temperature range depends on the tool
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
Tip Type	WT
UPC	037103312365
USB	Yes
Vacuum	0,7 bar
Voltage	120V
Weight (Catalog)	5.60 kg
Product Family	Rework, Hot Air, Desoldering Stations