



WR3000M Kit 120V

Item No: WR3000MN

3-Channel Power Unit, 360 W (400 W)

KEY FEATURES

- + WR3M multi-channel, hot air, desoldering, soldering rework system
- + 400 watts of power over 3 independently-controlled channels
- + Application flexibility with up to 21 tool options
- + PC Connectivity and data logging software included

TECHNICAL DATA

Length	11 in
Dimensions L x W x H	280.0 x 240.0 x 103.0mm
Automatic Tool Identification	Yes
Capacity (l/min)	18 l/min
Desoldering	Yes
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3.5mm pawl socket on back of device (hard-grounded)
ESD Safe	Yes
Hot Air (picto)	Yes
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	3
Overcurrent Release	2.0 A
Power	400 W
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range (Depends on Tool)	93 - 454°C (200 - 850 °F)
Temperature Range °C	93 - 454 °C
Temperature Range °F	200 - 850 °F
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
Tip Type	WT
UPC	037103304001
USB	Yes
Vacuum	0.7 bar (79 kPA) (8 psi)
Weight (Catalog)	7.30 kg
Product Family	Rework, Hot Air, Desoldering Stations