



WR3M 120V

Item No: WR3MN 3-Channel Power Unit, 360 W (400 W)

KEY FEATURES

Simoultaneous operation of up to 3 soldering tools

TECHNICAL DATA

Length	11 in
Dimensions L x W x H	280.0 x 240.0 x 103.0mm
Automatic Tool Identification	Yes
Capacity (I/min)	18 l/min
Desoldering	Yes
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3.5mm pawl socket on back of device (hard-grounded)
ESD Safe	Yes
Hot Air (picto)	Yes
Interface	USB
IPC Compliant	(Tip to Ground) Corresponds to IPC-J-001
Maximum Hot Air Flow Rate I/min (Depends on Tool)	15 l/min
Noise level (distance 1 m) dB(A)	0.7 bar
Number of Channels	3
Overcurrent Release	2.0 A
Power	360 W (400 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Range (Depends on Tool)	93 - 454°C (200 - 850 °F)
Temperature Range °C	93 - 454 °C
Temperature Range °F	200 - 850 °F
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
Tip Type	WT
UPC	037103303943
Vacuum	0.7 bar (79 kPA) (8 psi)
Voltage	120V
Weight (Catalog)	7.30 kg
Product Family	Rework, Hot Air, Desoldering Stations