

WXR3003 Kit 120V



Item No: WXR3003N

3-Channel Rework Station, 420 W
(600 W)

KEY FEATURES

- + Power unit WXR 3, 3 channels with WXHAP 200 Hot air iron, WXDV 120 Desoldering iron and WXP 65 Soldering iron
- + Compatible with all WX tools, accessories and peripherals

TECHNICAL DATA

| | |
|---|--|
| Length | 10.7 in |
| Dimensions L x W x H | 273.0 x 235.0 x 102.0mm |
| Capacity (l/min) | 18 l/min |
| Equipotential Bonding Socket | Via 3.5mm pawl socket on back of device (hard-grounded) |
| ESD Safe | Yes |
| Interface | 1x USB, 2x RS232, 2x Switching Output |
| IPC Compliant | Yes |
| Maximum Hot Air Flow Rate l/min (Depends on Tool) | 15 l/min |
| Noise level (distance 1 m) dB(A) | 0.7 bar |
| Number of Channels | 3 |
| Overcurrent Release | 2.0 A |
| Power | 420 W (600 W) |
| Temperature Accuracy °C | ± 9°C |
| Temperature Accuracy °F | ± 17°F |
| Temperature Accuracy for Hot Air | ± 30°C, ± 54°F |
| Temperature Range °C | 100 - 450 °C (550 °C) |
| Temperature Range °F | 200 - 850 °F (999 °F) |
| Temperature Stability °C | ± 2°C |
| Temperature Stability °F | ± 4°F |
| Tip Type | WX |
| UPC | 037103304285 |
| USB | USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types |
| Voltage | 120V |
| Weight (Catalog) | 6.70 kg |
| Product Family | Rework, Hot Air, Desoldering Stations |