

WXR3 120V

Item No: WXR3N
3-Channel Power Unit, 420 W (600 W)

KEY FEATURES

- All-in-one-Station
- Benchtop controller capability e.g. Zero Smog Systems
- Automatic tool recognition and power management
- Compatible with all WX tools
- Storage medium in hand piece
- Blue LED backlighting
- Multilingual menu navigation

TECHNICAL DATA

Length	10.7 in
Dimensions L x W x H	273.0 x 235.0 x 102.0mm
Automatic Tool Identification	Yes
Benchtop Controller	Yes
Capacity (l/min)	18 l/min
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3.5mm pawl socket on back of device (hard-grounded)
ESD Safe	Yes
Fuse	2.0A
Interface	1x USB, 2x RS232, 2x Switching Output
IPC Compliant	Yes
Maximum Hot Air Flow Rate l/min (Depends on Tool)	15 l/min
Multilingual Display	Yes
Number of Channels	3
Power	420 W (600 W)
Temperature Accuracy °C	± 9°C
Temperature Accuracy °F	± 17°F
Temperature Accuracy for Hot Air	± 30°C, ± 54°F
Temperature Stability °C	± 2°C
Temperature Stability °F	± 4°F
Traceability	Yes
UPC	037103304254
USB	USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types
Weight (Catalog)	6.70 kg
Product Family	Rework, Hot Air, Desoldering Stations