



## ZeroSmog Guard Light 120 V

Item No: FT91020299

ZeroSmog Guard Light - Single User  
Filtration Unit 60 W, 120 V

ZeroSmog Unit Guard Light, 120 V  
1 x main filter (HEPA H13 and  
Activated Carbon)  
5 x ePM1-75% prefilters

## KEY FEATURES

- + Highest level filtration – for cleaner and healthier air**
  - High efficiency particle and gas filtration
  - Odour removal during soldering
  - Powerful blower maintains suction pressure throughout the filter's life
  - High flow rate to collect all the smoke
  - Quiet - lowest noise level on the market – less than 50dB
  - Easy main and pre-filter change
  - Low maintenance
  - Easy-to-reach on/off switch
  - ESD safe
  - Retains Weller Easy-Click 60 Hose system
- + Clean & Healthy Air**
  - Provides superior air quality through high-efficiency filtration of soldering particles and gases with a large filtering surface (H13 HEPA particle filter, activated carbon).
- + Superior Experience**
  - Lowest noise level on the market ensures a healthy, pleasant, and comfortable working environment.
- + Quick and Easy Filter Change**

Ensures user convenience with fast, hassle-free replacements of both, prefilter and main filter.

- + **Compact Design**  
Saves space with a compact, under-the-bench design ideal for single-user use.
- + **Powerful Extraction**  
The robust blower maintains sufficient suction pressure throughout the filter's life, ensuring a high flow rate to capture all smoke effectively.
- + **Single User Entry Level Filtration Unit**  
60 W, 120 V  
Highest level filtration – for cleaner and healthier air  
High efficiency particle and gas filtration  
Odour removal during soldering  
Powerful blower maintains suction pressure throughout the filter's life  
High flow rate to collect all the smoke  
Quiet - lowest noise level on the market – less than 50dB  
Easy main and pre-filter change  
Low maintainance  
Easy-to-reach on/off switch  
ESD safe  
Retains Weller Easy-Click 60 Hose system
- + **ZeroSmog Unit Guard Light, 120 V**  
1 x main filter (HEPA H13 and Activated Carbon)  
5 x ePM1-75% prefilters

Clean air is a worker's right.  
ZeroSmog Guard



## TECHNICAL DATA

Dimensions L x W x H	270 x 336 x 435 mm 10.63 x 13.23 x 17.13 in
ESD Safe	Yes
Maximum Capacity	100 (m <sup>3</sup> /h)
Maximum Vacuum	2700 Pa/V
Noise level (distance 1 m) dB(A)	less than 50 dBA
Power	60 W (100-120 V~)
UPC	037103378804
Voltage	100-120V (50/60 Hz)
Weight (Catalog)	9.5 kg
Product Family	Solder Fumes Volume Extraction 1-2 Workstations